

Welding 20 bar

For the SWIVELLING version add the suffix "/SO" at the P/N.
For example:
430/70/SO

FIXED PAINTED STEEL



Supplied with:

- double hose Standard EN ISO 3821, hose SBR/EPDM rubber with brass coupling
- brass swivel joint
- Viton® seals
- central shaft in galvanized steel
- inlet hose 1,5 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	Double hose supplied	Connection	
			Inlet	Outlet
S. 430	430/70	without hose	M 3/8"G	M 3/8"G
	430/71	13m 2x1/4"-2x6 (993/13)	F 3/8"G	F 3/8"G
	430/72	12m 2x5/16"-2x8 (994/12)	F 3/8"G	F 3/8"G
S. 530	530/70	without hose	M 3/8"G	M 3/8"G
	530/71	17m 2x1/4"-2x6 (993/17)	F 3/8"G	F 3/8"G
	530/72	20m 2x1/4"-2x6 (993/20)	F 3/8"G	F 3/8"G
	530/73	15m 2x5/16"-2x8 (994/15)	F 3/8"G	F 3/8"G
	530/74	20m 2x5/16"-2x8 (994/20)	F 3/8"G	F 3/8"G
	530/75	15m 2x3/8"-2x9 (995/15)	F 3/8"G	F 3/8"G
S. 540	540/70	without hose	M 3/8"G	M 3/8"G
	540/71	25m 2x1/4"-2x6 (993/25)	F 3/8"G	F 3/8"G
	540/72	30m 2x1/4"-2x6 (993/30)	F 3/8"G	F 3/8"G
	540/73	35m 2x1/4"-2x6 (993/35)	F 3/8"G	F 3/8"G
	540/74	25m 2x5/16"-2x8 (994/25)	F 3/8"G	F 3/8"G
	540/75	30m 2x5/16"-2x8 (994/30)	F 3/8"G	F 3/8"G
	540/76	35m 2x5/16"-2x8 (994/35)	F 3/8"G	F 3/8"G
	540/77	20m 2x3/8"-2x9 (995/20)	F 3/8"G	F 3/8"G
	540/78	25m 2x3/8"-2x9 (995/25)	F 3/8"G	F 3/8"G
	540/79	27m 2x3/8"-2x9 (995/27)	F 3/8"G	F 3/8"G



Atex 94/9 ▶ II 3GD c (T5) T100°C X

USES

