



Straight Fitting with 24° Taper / O-Ring Type FI-SNV - Series S



Series	Tube OD mm D1	PN bar	Dimensions mm D2	L1	L2	S1	Weight kg ca. per 100	Ordering Codes
S	6	800	3	30,3	33	17	4,21	FI-SNV-06S-V-W3-DK0-GLB
	6	800	3	37	39,7	17	4,52	FI-SNV-06S-V-W3-DK0
	6	800	3	37,8	40,5	17	0,46	FI-SNV-06S-V-W3-DK0-GLA
	8	800	4	31,3	34	19	5,63	FI-SNV-08S-V-W3-DK0-GLB
	8	800	4	37	39,7	19	6,03	FI-SNV-08S-V-W3-DK0
	8	800	4	37,8	40,5	19	6,13	FI-SNV-08S-V-W3-DK0-GLA
	10	800	6	32,2	35	22	7,63	FI-SNV-10S-V-W3-DK0-GLB
	10	800	6	41	43,8	22	8,39	FI-SNV-10S-V-W3-DK0
	12	630	8	35,2	38	24	6,52	FI-SNV-12S-V-W3-DK0-GLB
	12	630	8	42	44,8	24	10,51	FI-SNV-12S-V-W3-DK0
	14	630	9	37,2	41	27	2,9	FI-SNV-14S-V-W3-DK0-GLB
	14	630	9	45	48,8	27	13,9	FI-SNV-14S-V-W3-DK0
	16	630	10	37,2	42	30	16,09	FI-SNV-16S-V-W3-DK0-GLB
	16	630	10	46	50,8	30	17,57	FI-SNV-16S-V-W3-DK0
	20	420	13	42	48	36	26,3	FI-SNV-20S-V-W3-DK0-GLB
	20	420	13	55	61	36	24,36	FI-SNV-20S-V-W3-DK0
	25	420	18	45,5	54,4	46	45,05	FI-SNV-25S-V-W3-DK0-GLB
	25	420	18	56,5	65,4	46	50,1	FI-SNV-25S-V-W3-DK0-GLA
	25	420	18	58	67	46	49,45	FI-SNV-25S-V-W3-DK0
	30	420	20	50	62	50	57,2	FI-SNV-30S-V-W3-DK0-GLB
	30	420	20	62	74	50	61,4	FI-SNV-30S-V-W3-DK0
	38	420	30	50	67	60	74,2	FI-SNV-38S-V-W3-DK0-GLB
	38	420	30	67	84	60	86,7	FI-SNV-38S-V-W3-DK0

Standard seal material is FKM (Viton®).

Ordering Codes

FI-SNV-10*S*-V*-W3*-DK0

* Straight Fitting with 24° Taper / O-Ring (DKO)	FI-SNV
* Outside Tube Diameter D1 (in mm)	-10
* Series	Light Series (page 138) Heavy Series (page 139)
	L S
* Seal Material	FKM (Viton®)
	-V
* Material Code	Steel, zinc/nickel-plated
	-W3
Please contact STAUFF for alternative materials and surface finishings.	
* Assembling / Kitting	Fitting body supplied with swivel nuts and O-rings
	-DK0
* Total length	dimension see table
	-GLA
	-GLB

Spare Parts / Accessories



O-Ring
Type **O-RING**

Page 239

