



TW-Kupplung Typ MK mit BSPP - Innengewinde (Komplett)

mit CSM Lippendichtung und PTFE Gewindedichtung

Female coupler type MK BSPP female thread (complete) - CSM lip gasket PTFE thread-tasket
 Raccord type MK taraudé femelle BSPP (Complet) - Joint CSM pour raccord - Joint de fi letage PTFE
 TW-Acople hembra tipo MK con rosca hembra BSPP (completo) - Junta labial CSM Junta de rosca de PTFE
 TW Gniazdo typ MK z gwintem wewnętrznym BSPP (kompletny) - Uszczelka profilowa CSM Uszczelka o-ring PTFE
 TW-Tipo MK con filettato femmina BSPP (completo) - CSM, guarnizione filetatto PTFE

Part-No.	Material	WP	Dimension	Thread	Price
2MKS	SS 1.4408	16 bar	DN50	G2"	
3MKS	SS 1.4408	16 bar	DN80	G3"	
4MKS **	SS 1.4408	16 bar	DN100	G4"	

**einteilig - mit O-Ring statt Lippendichtung
 one pice - with O-ring instead of lip gasket

TW - Kupplung Typ MK mit BSPP - Innengewinde (Komplett) PFA ausgekleidet

mit FKM Lippendichtung

Female coupler type MK BSPP female thread (complete) PFA coated - FKM lip gasket
 Raccord type MK taraudé femelle BSPP (Complet) Revêtu de PFA - Joint pour raccord FKM
 TW- Acople hembra tipo MK con rosca hembra BSPP (completo) Recubierto de PFA - Junta FKM
 TW Gniazdo typ MK z gwintem wewnętrznym BSPP (kompletny) Z powłoką PFA - Uszczelka profilowa FKM
 TW - Tipo MK con filettato femmina BSPP (completo) Rivestimento in PFA - guarnizione FKM

NEW



Part-No.	Material	WP	Shank	Thread	Price
2MKSPFA-W	SS 1.4408 PFA white coated	25 bar	DN50	G2"	
3MKSPFA-W	SS 1.4408 PFA white coated	25 bar	DN80	G3"	
4MKSPFA-W**	SS 1.4408 PFA white coated	25 bar	DN100	G4"	
2MKSPFA-B	SS 1.4408 PFA black coated	25 bar	DN50	G2"	
3MKSPFA-B	SS 1.4408 PFA black coated	25 bar	DN80	G3"	
4MKSPFA-B**	SS 1.4408 PFA black coated	25 bar	DN100	G4"	

**einteilig - mit O-Ring statt Lippendichtung
 one pice - with O-ring instead of lip gasket

