

Medium Pressure

EHA501

Medium Duty Air



Application

- Medium duty air service and pneumatic tools

Markets

- Construction
- Mining
- Oil and gas exploration
- Drilling equipment
- Rental industry
- Steel
- Quarries

Construction

Tube Oil-mist resistant SBR rubber blend

Reinforcement

High-tensile synthetic textile

Cover Abrasion, ozone, and weather resistant SBR rubber blend

Colors Yellow (YW), Black (BK)

Certification

TS 745 - EN ISO 2398 Type 4,
2016 Type 2 Class A

Operating temperature

-25°C to +70°C
(-13°F to +158°F)

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	mtr	ft
EHA501-08YW	12.7	0.50	22.0	0.87	20.7	300	64.0	928	65	2.56	0.33	0.22	61	200
EHA501-10YW	16.0	0.62	25.0	0.98	20.7	300	64.0	928	80	3.15	0.37	0.25	61	200
EHA501-12YW	19.0	0.75	29.0	1.14	20.7	300	64.0	928	95	3.74	0.50	0.33	61	200
EHA501-16YW	25.4	1.00	36.0	1.42	20.7	300	64.0	928	125	5.12	0.67	0.45	61	200
EHA501-20YW	32.0	1.25	44.0	1.73	20.7	300	64.0	928	300	11.81	0.96	0.64	61	200
EHA501-24YW	38.0	1.50	51.0	2.01	20.7	300	64.0	928	360	14.17	1.18	0.79	61	200
EHA501-28YW	44.5	1.75	60.0	2.36	20.7	300	64.0	928	400	15.75	1.63	1.10	61	200
EHA501-32YW	50.8	2.00	65.0	2.56	20.7	300	64.0	928	450	17.71	1.66	1.11	61	200
EHA501-40YW	63.5	2.50	80.0	3.15	20.7	300	64.0	928	600	23.62	2.45	1.65	61	200
EHA501-48YW	76.2	3.00	92.0	3.62	20.7	300	64.0	928	750	29.53	2.65	1.78	61	200
EHA501-64YW	101.6	4.00	118.0	4.65	20.7	300	64.0	928	1000	39.37	3.81	2.56	61	200