



Thanks to the exclusive design of the housing and the high-strength screw, the ASFA L Worm-Drive Clip has excellent performance while being at the same time very compact.

The cold-formed stamped 9 mm band, smoothed on the underside, combined with the bevelled band edges protects the hose from any damage.

DIN 3017. The ASFA LW1 hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

MATERIAL: Band and support: W2
Stainless steel X6Cr17
DIN 1.4016 AISI 430
Bolt: Steel Qst 36-3
DIN 1.0214

FINISH: Bolt: Zinc plated Cr3

CORROSION RESISTANCE: 72 hours salt spray
(ASTM B-117)

Ø Application mm	Part Number	L +1-0.5	T ±0.1	H Max.	B Max.	S Min.	Max. Pressure Bar	Box Quantity	Outer Box Quantity
8-12(*)	03016508	18,5	0,4	9,2	11,5	15,0	15	200	1.600
8-16	03016516	22,1	0,6	10,5	14,0	15,0	45	200	800
12-22	03016524	22,1	0,6	10,5	14,0	15,0	45	200	800
16-27	03016532	23,6	0,7	10,5	14,0	16,5	42	200	800
20-32	03016540	23,6	0,7	10,5	14,0	16,5	36	200	800
20-35	03016698	23,6	0,7	10,5	14,0	16,5	36	100	800
25-40	03016559	25,6	0,7	10,5	14,0	17,1	32	100	400
30-45	03016567	25,6	0,7	10,5	14,0	17,1	28	100	800
32-50	03016575	25,6	0,7	10,5	14,0	17,1	24	100	800
40-60	03016583	25,6	0,7	10,5	14,0	17,1	19	100	400
50-70	03016591	29,6	0,7	10,5	14,0	21,1	17	100	100
60-80	03016604	29,6	0,7	10,5	14,0	21,1	15	100	100
70-90	03016612	29,6	0,7	10,5	14,0	21,1	13	50	400
80-100	03016620	29,6	0,7	10,5	14,0	21,1	11	50	50
90-110	03016639	29,6	0,7	10,5	14,0	21,1	10	25	200
100-120	03016647	29,6	0,7	10,5	14,0	21,1	9	25	200
110-130	03016655	29,6	0,7	10,5	14,0	21,1	8	25	25
120-140	03016663	29,6	0,7	10,5	14,0	21,1	7	25	25
130-150	03016671	29,6	0,7	10,5	14,0	21,1	6	25	25
140-160	03016680	29,6	0,7	10,5	14,0	21,1	5	25	25

(*) ASFA-L 7 mm