

ORFS 45° ORFS 45°


Amerikanisches Normgewinde UN-UNS

Abdichtung: flachdichtender Nippel mit Überwurfmutter

American standard thread UN-UNS

Sealing: flat sealing hose nipple with union nut

PN (bar)	Dash	DN	Inch	Gewinde (G) Thread (G)	H (mm)	K (mm)	L (mm)	SW (mm) AF (mm)	Art.-Nr. Item-No.
450	-04	6	1/4"	9/16"-18 UNF	32,5	10,5	60,5	17	424 66 06 91
450	-04	6	1/4"	11/16"-16 UN	34,5	12,5	62,5	22	424 66 06 92
350	-05	8	5/16"	9/16"-18 UNF	33,5	11	61,5	17	424 66 08 91
350	-05	8	5/16"	11/16"-16 UN	35	12,5	63	22	424 66 08 92
450	-06	10	3/8"	9/16"-18 UNF	35	11,5	65,5	17	424 66 10 91
450	-06	10	3/8"	11/16"-16 UN	36	12,5	66,5	22	424 66 10 92
450	-06	10	3/8"	13/16"-16 UN	38,5	15	69	24	424 66 10 93
420	-08	12	1/2"	13/16"-16 UN	42,5	15,5	75,5	24	424 66 12 93
420	-08	12	1/2"	1"-14 UNS	45	17,5	78	30	424 66 12 94
420	-08	12	1/2"	1 3/16"-12 UN	47	20,5	80	36	424 66 12 95
350	-10	16	5/8"	1"-14 UNS	49	18	85	30	424 66 16 94
350	-10	16	5/8"	1 3/16"-12 UN	51,5	20,5	78,5	36	424 66 16 95
350	-12	19	3/4"	1 3/16"-12 UN	58	21	99	36	424 66 20 95
350	-12	19	3/4"	1 7/16"-12 UN	60,5	23,5	101	41	424 66 20 96
280	-16	25	1"	1 7/16"-12 UN	73	24	124	41	424 66 25 96
280	-16	25	1"	1 11/16"-12 UN	75	26,5	126	50	424 66 25 97
210	-20	31	1 1/4"	1 11/16"-12 UN	84	27	142	50	424 66 32 97
185	-24	38	1 1/2"	2"-12 UN	98	30	163	60	424 66 40 98



ORFS 90° ORFS 90°

Amerikanisches Normgewinde UN-UNS

Abdichtung: flachdichtender Nippel mit Überwurfmutter

American standard thread UN-UNS

Sealing: flat sealing hose nipple with union nut

PN (bar)	Dash	DN	Inch	Gewinde (G) Thread (G)	H (mm)	K (mm)	L (mm)	SW (mm) AF (mm)	Art.-Nr. Item-No.
450	-04	6	1/4"	9/16"-18 UNF	27	21	55	17	424 67 06 91
450	-04	6	1/4"	11/16"-16 UN	27	24	55	22	424 67 06 92
350	-05	8	5/16"	9/16"-18 UNF	29	23	57	17	424 67 08 91
350	-05	8	5/16"	11/16"-16 UN	29	25	57	22	424 67 08 92
450	-06	10	3/8"	9/16"-18 UNF	30	22	60,5	17	424 67 10 91
450	-06	10	3/8"	11/16"-16 UN	31,5	24,5	62	22	424 67 10 92
450	-06	10	3/8"	13/16"-16 UN	31	30	61	24	424 67 10 93
415	-08	12	1/2"	11/16"-16 UN	35	32	68	22	424 67 12 92
420	-08	12	1/2"	13/16"-16 UN	39	31	72	24	424 67 12 93
420	-08	12	1/2"	1"-14 UNS	39	34	72	30	424 67 12 94
420	-08	12	1/2"	1 3/16"-12 UN	39	42	72	36	424 67 12 95
350	-10	16	5/8"	1"-14 UNS	45	35	81	30	424 67 16 94
350	-10	16	5/8"	1 3/16"-12 UN	45	42	81	36	424 67 16 95
350	-12	19	3/4"	1 3/16"-12 UN	55	45	95	36	424 67 20 95
350	-12	19	3/4"	1 7/16"-12 UN	55	49	95	41	424 67 20 96
280	-16	25	1"	1 7/16"-12 UN	71	55	122	41	424 67 25 96
280	-16	25	1"	1 11/16"-12 UN	71	58	122	50	424 67 25 97
210	-20	31	1 1/4"	1 11/16"-12 UN	86	63	143	50	424 67 32 97
185	-24	38	1 1/2"	2"-12 UN	102	73	167	60	424 67 40 98

