

INDUSTRIAL HOSE STEAM

PREMIUM™ STEAM MASTER



mm	mm	mm	MPa	MPa	mm	kg/100m	m	REF.
13	25	6.0	1.8	18.0	91	50	40	STEAM MAS 13mm x CL40
16	30	7.0	1.8	18.0	112	70	40	STEAM MAS 16mm x CL40
19	33	7.0	1.8	18.0	133	80	40	STEAM MAS 19mm x CL40
25	40	7.5	1.8	18.0	175	110	40	STEAM MAS 25mm x CL40
32	48	8.0	1.8	18.0	224	150	40	STEAM MAS 32mm x CL40
38	54	8.0	1.8	18.0	266	180	40	STEAM MAS 38mm x CL40
51	67	8.0	1.8	18.0	357	230	40	STEAM MAS 51mm x CL40

RECOMMENDED FOR	Premium steam hose for the transport of pressurised saturated steam at +210°C up to a max. 18 bar working pressure or pressurised hot water.
TUBE	Black EPDM, smooth, conductive.
REINFORCEMENT	Two high tensile steel braids.
COVER	EPDM rubber, smooth, black, all sizes are pinpricked. Extremely weather resistant cover.
TEMPERATURE RANGE	-40°C to +210°C.
BURST PRESSURE	180 bar.
ELECTRICALLY CONDUCTIVE	$R < 10^6 \text{ Ohm}$.
STANDARDS	EN ISO 6134:2005-2A.
BRANDING TRANSFER LABEL	PREMIUM™ STEAM MASTER - EN ISO 6134:2005-2A STEAM 18 BAR 210°C Q - DRAIN AFTER USE
BRANDING EMBOSSED LABEL	GATES PREMIUM™ STEAM MASTER - EN ISO 6134:2005-2A STEAM 18 BAR - DIAM mm - Q - Q - year