

Flachdichtungen Flat Gaskets



für Festkupplungen mit Innengewinde

Gummi: schwarz oder weiß

for adapters with female thread

Rubber: black or white



Abmessung Measurement (mm)	Gummi (Euro) Rubber	Silikon (Euro) Silicone rubber	Teflon (Euro) PTFE virginial
R ½" Ø 22/17 x 2	91-003050-00		
R ¾" Ø 27/18 x 2	91-003075-00		
R 1" Ø 33/20 x 3	91-003100-00	91-003100-02	91-003100-03
R 1¼" Ø 42/33 x 3	91-003125-00		91-003125-03
R 1½" Ø 48/39 x 3	91-003150-00		91-003150-03
R 2" Ø 60/47 x 3	91-003200-00	91-003200-02	91-003200-03
R 2½" Ø 76/66 x 3	91-003250-00		91-003250-03
R 3" Ø 88/76 x 3	91-003300-00	91-003300-02	91-003300-03
R 3½" Ø 101/89 x 3	91-003350-00		
R 4" Ø 113/102 x 3	91-003400-00	91-003400-02	91-003400-03
R 4½" Ø 126/105 x 3	91-003450-00		91-003450-03
R 5" Ø 140/122 x 4	91-003500-00		91-003500-03
R 6" Ø 165/140 x 4	91-003600-00		91-003600-03
R 8" Ø 216/190 x 5	91-003800-00		
R 10" Ø 267/240 x 5	91-003999-00		

Flachdichtungen für Deckkapseln Flat Gaskets for end caps



Größe Size	Abmessung Measurement (mm)	Werkstoff Material	Weight (kg)	Ident-No.	Euro
für Deckkapsel C	Ø 58 / 46 x 4	Gummi - rubber	0,005	91-004066-00	
für Deckkapsel 65	Ø 75 / 54 x 3	Gummi - rubber	0,007	91-004081-00	
für Deckkapsel B	Ø 78 / 61 x 4	Gummi - rubber	0,011	91-004089-00	
für Deckkapsel A	Ø 119 / 100 x 4	Gummi - rubber	0,018	91-004133-00	

	Nitril	Silikon	Viton	EPDM
Temperatur Temperature	- 40° C + 110° C	- 60° C + 180° C	- 15° C + 200° C	- 35° C + 130° C
lebensmittelbeständig resistant to food	weiß white	ja yes	nein no	nein no
fett- / ölbeständig resistant to grease / oil	bedingt partly	nein no	ja yes	nein no