

Dichtungen für SAE-Flansche

Sealings for SAE flanges

Werkstoff: Polyurethan (WUAQ 3), 93 Shore A

Temperaturbereich: -30 °C bis +100 °C

Material: polyurethane (WUAQ 3), 93 Shore A

Temperature range: -30 °C up to +100 °C

Flansch Flange	Außen-Ø (mm) Outer-Ø (mm)	Höhe (mm) Height (mm)	Stärke (mm) Thickness (mm)	Art.-Nr. Item-No.
1/2"	25,6	3,5	3,8	425 81 12 34
3/4"	31,8	3,5	3,8	425 81 20 36
1"	39,8	3,5	3,8	425 81 25 37
1 1/4"	44,8	3,5	3,8	425 81 32 38
1 1/2"	54,3	3,5	3,8	425 81 40 39
2"	63,8	3,5	3,8	425 81 50 40
2 1/2"	77	3,5	3,8	425 81 63 63
3"	91,0	3,5	3,8	425 81 76 76



Dichtungen für Supercatflansche

Sealings for Supercat flanges

Achtung: nur für Cat-Armaturensystem 428

Werkstoff: NBR, 90 Shore

Attention: only for Cat-fitting system 428

Material: NBR, 90 shore

Flansch Flange	D (mm)	H (mm)	S (mm)	Art.-Nr. Item-No.
3/4"	25,4	5	3,5	425 82 20 36
1"	31,8	5	3,5	425 82 25 37
1 1/4"	38,1	5	3,5	425 82 32 38
1 1/2"	44,5	5	3,5	425 82 40 39
2"	63,9	5	3,5	425 82 50 40

