


JIC FJX90

Female JIC swivel. 37° inverted cone.

90° swept elbow.




D				A	B	E	H1	H2	REF.
-size	DN	"		mm	mm	mm	mm	mm	GSM
-24	40	1.1/2	1.7/8" - 12 UN	227.5	132.3	86.0	60.0	55.0	24GSM24FJX90M

-24 size is 35.0 MPa (5000 psi). / M: Medium drop per ISO 12151-5.

JIC MJ

Male JIC parallel. 37° cone.




D				A	B	H	REF.
-size	DN	"		mm	mm	mm	GSM
-24	40	1.1/2	1.7/8" - 12 UN	162.3	67.3	50.0	24GSM24MJ
-32	50	2	2.1/2" - 12 UN	196.2	82.2	65.0	32GSM32MJ

-24 to -32 size are 35.0 MPa (5000 psi).

SAE FFORX

Female SAE flat face 'O' ring swivel.



D				A	B	H1	H2	REF.
-size	DN	"		mm	mm	mm	mm	GSM
-24	40	1.1/2	2" - 12 UN	164.4	69.4	60.0	55.0	24GSM24FFORX

-24 size is 28.0 MPa (4000 psi).

Unless otherwise stated the coupling meets the pressure rating requirements of the respective international standard.