

1:1

PUR Hose Kits – with Series 320

CEJN Original, Eurostandard 7.4 mm

- Series 320 couplings and nipples
- Flexible PUR hose with long service life
- Pre-assembled and ready to use

CEJN Hose Kits come pre-assembled and ready for immediate use. They consist of an extremely flexible, straight braided or spiral polyurethane (PUR) hose combined with Series 320 Standard or eSafe couplings and nipples with reusable Stream-Line connections.

PUR Hose Kits are also available with Series 300, 310 and 410 Standard or Vented Safety couplings and nipples.



Flow capacity is measured at 100 PSI (6.9 bar) inlet pressure, and pressure drop at 6 PSI (0.4 bar).

		Service length	Part No.	ID x OD	Max working pressure	
SERIES 320	Spiral	6.6 °F (2.0 m)	19 958 9907	(5 x 8 mm)	145 PSI (10 bar)	
			19 958 9910	(6.5 x 10 mm)	145 PSI (10 bar)	
			19 958 9914	(8 x 12 mm)	145 PSI (10 bar)	
			19 958 9917	(11 x 16 mm)	145 PSI (10 bar)	
		13.1 °F (4.0 m)	19 958 9903	(5 x 8 mm)	145 PSI (10 bar)	
			19 958 9904	(6.5 x 10 mm)	145 PSI (10 bar)	
			19 958 9905	(8 x 12 mm)	145 PSI (10 bar)	
			19 958 9906	(11 x 16 mm)	145 PSI (10 bar)	
		19.7 °F (6.0 m)	19 958 9908	(5 x 8 mm)	145 PSI (10 bar)	
			19 958 9912	(6.5 x 10 mm)	145 PSI (10 bar)	
	19 958 9915		(8 x 12 mm)	145 PSI (10 bar)		
	19 958 9918		(11 x 16 mm)	145 PSI (10 bar)		
	Straight Braided	32.8 °F (10.0 m)	19 958 9909	(5 x 8 mm)	145 PSI (10 bar)	
			19 958 9913	(6.5 x 10 mm)	145 PSI (10 bar)	
			19 958 9916	(8 x 12 mm)	145 PSI (10 bar)	
			19 958 9919	(11 x 16 mm)	145 PSI (10 bar)	
		49.2 °F (15.0 m)	19 958 9829	(8 x 12 mm)	232 PSI (16 bar)	
			19 958 9339	(9.5 x 13.5 mm)	232 PSI (16 bar)	
			19 958 9737	(11 x 16 mm)	174 PSI (12 bar)	
			19 958 9830	(8 x 12 mm)	232 PSI (16 bar)	
SERIES 320, ESAFE		Spiral	6.6 °F (2.0 m)	19 958 9763	(6.5 x 10 mm)	145 PSI (10 bar)
				19 958 9762	(8 x 12 mm)	145 PSI (10 bar)
	19 958 9767			(11 x 16 mm)	145 PSI (10 bar)	
	19 958 9764			(6.5 x 10 mm)	145 PSI (10 bar)	
	13.1 °F (4.0 m)		19 958 9706	(8 x 12 mm)	145 PSI (10 bar)	
			19 958 9768	(11 x 16 mm)	145 PSI (10 bar)	
19.7 °F (6.0 m)	19 958 9765	(6.5 x 10 mm)	145 PSI (10 bar)			
	19 958 9707	(8 x 12 mm)	145 PSI (10 bar)			
	19 958 9769	(11 x 16 mm)	145 PSI (10 bar)			
	26.2 °F (8.0 m)	19 958 9766	(6.5 x 10 mm)	145 PSI (10 bar)		
19 958 9708		(8 x 12 mm)	145 PSI (10 bar)			
19 958 9770		(11 x 16 mm)	145 PSI (10 bar)			
Straight Braided		32.8 °F (10.0 m)	19 958 9738	(11 x 16 mm)	174 PSI (12 bar)	
	19 958 9341		(9.5 x 13.5 mm)	232 PSI (16 bar)		
	19 958 9342		(9.5 x 13.5 mm)	232 PSI (16 bar)		



CEJN reserves the right to make changes without further notification. Thread connections are listed according to ISO Standards. Other connections and sealing material on request. Check with an authorized CEJN distributor for availability and prices. Some part numbers may be subject to minimum order quantities. Please visit our website, www.cejn.com, for general maintenance tips.

AIR FLOW

- HOSE 5X8 MM
- HOSE 6.5X10 MM
- HOSE 8X12 MM
- HOSE 9.5X13.5 MM
- HOSE 11X16 MM

