



## CONFIGURATION

<input checked="" type="checkbox"/>	Control	All Ports Blocked
<input checked="" type="checkbox"/>	Adjustment Range	-
<input checked="" type="checkbox"/>	Seal Material	Buna-N
<input type="checkbox"/>	(none) Material/Coating	

This cavity plug blocks all ports.

## TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-8A
Series	P
Maximum Operating Pressure	5000 psi
Port Configuration	2 Port
Valve Hex Size	7/8 in.
Valve Installation Torque	20 - 25 lbf ft
Seal kit - Cartridge	Buna: 990008007
Seal kit - Cartridge	EPDM: 990008014
Seal kit - Cartridge	Polyurethane: 990008002
Seal kit - Cartridge	Viton: 990008006
Model Weight	0.11 lb.

## CONFIGURATION OPTIONS

### Model Code Example: XACAXXX

CONTROL	(X) ADJUSTMENT RANGE	(X) SEAL MATERIAL	(N) MATERIAL/COATING
<input checked="" type="checkbox"/> All Ports Blocked	<input checked="" type="checkbox"/> -	<input checked="" type="checkbox"/> Buna-N	<input type="checkbox"/> Standard Material/Coating
		<input type="checkbox"/> EPDM	<input type="checkbox"/> /AP Stainless Steel, Passivated
		<input type="checkbox"/> Viton	

## TECHNICAL FEATURES

- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.

## RELATED MODELS

- [XACAE](#) Port 1 to external port, port 2 blocked cavity plug