


Safety Locking Plate


(for Use with Stacking Bolt AF)

Type SIG


A



STAUFF Group 1



STAUFF Group 1A to 8 (7M / 8M)



Group STAUFF	DIN	Dimensions (mm/in)				Ordering Codes (Standard Options)
		L	B1	B2	S	
1	0	16	32	11,2	1	SIG-1-W3
		.63	1.26	.44	.04	
1A	1	33	28	11,2	1	SIG-1A-W3
		1.30	1.10	.44	.04	
2	2	39	28	11,2	1	SIG-2-W3
		1.54	1.10	.44	.04	
3	3	47	28	11,2	1	SIG-3-W3
		1.85	1.10	.44	.04	
4	4	56	28	11,2	1	SIG-4-W3
		2.20	1.10	.44	.04	
5	5	69	28	11,2	1	SIG-5-W3
		2.72	1.10	.44	.04	
6	6	85	28	11,2	1	SIG-6-W3
		3.35	1.10	.44	.04	
7	7	117	28	11,2	1	SIG-7-W3
		4.61	1.10	.44	.04	
8	8	143	28	11,2	1	SIG-8-W3
		5.63	1.10	.44	.04	
7M		125	40	15,2	5	SIG-7M-W3
		4.92	1.57	.60	.20	
8M		160	45	15,2	5	SIG-8M-W3
		6.30	1.77	.60	.20	


Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

Ordering Codes

Safety Locking Plate

***SIG-*1-*W3**

* Safety Locking Plate		SIG
* STAUFF Group		1
* Material code	Carbon Steel, zinc/nickel-plated	W3
	Stainless Steel V2A	
	1.4301 / 1.4305 (AISI 304 / 303)	W4
	Stainless Steel V4A	
	1.4401 / 1.4571 (AISI 316 / 316 Ti)	W5



Group STAUFF	DIN	Dimensions (mm/in)					Ordering Codes (Standard Options)
		Thread G	L1	L2	L3 min.	Hex	
1	0	M6 1/4-20 UNC	34 1.34	20 .79	12 .47	11 .43	AF-1/1A/1D-M-W3 AF-1/1A/1D-U-W3
1A	1	M6 1/4-20 UNC	34 1.34	20 .79	12 .47	11 .43	AF-1/1A/1D-M-W3 AF-1/1A/1D-U-W3
2	2	M6 1/4-20 UNC	40 1.57	25 .98	12 .47	11 .43	AF-2-M-W3 AF-2-U-W3
3	3	M6 1/4-20 UNC	44 1.73	30 1.18	12 .47	11 .43	AF-3-M-W3 AF-3-U-W3
4	4	M6 1/4-20 UNC	49 1.93	35 1.38	12 .47	11 .43	AF-4-M-W3 AF-4-U-W3
5	5	M6 1/4-20 UNC	64 2.52	50 1.97	12 .47	11 .43	AF-5-M-W3 AF-5-U-W3
6	6	M6 1/4-20 UNC	74 2.91	60 2.36	12 .47	11 .43	AF-6-M-W3 AF-6-U-W3
7	7	M6 1/4-20 UNC	99 3.90	85 3.35	12 .47	11 .43	AF-7-M-W3 AF-7-U-W3
8	8	M6 1/4-20 UNC	124 4.88	110 4.33	12 .47	11 .43	AF-8-M-W3 AF-8-U-W3
7M		M10 3/8-16 UNC	115 4.53	90 3.54	15 .59	15 .59	AF-7M-M-W3 AF-7M-U-W3
8M		M10 3/8-16 UNC	150 5.91	125 4.92	15 .59	15 .59	AF-8M-M-W3 AF-8M-U-W3

All threaded parts are available with Metric ISO thread or unified coarse (UNC) thread according to dimension table.
Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

Stacking Bolt

(for Use with Safety Locking Plate SIG)

Type AF



Ordering Codes

Stacking Bolt

***AF-*1/1A/1D-*M-*W3**

* Type of bolt	Stacking Bolt	
	(according to STAUFF Standard)	AF
* STAUFF Group		1
* Thread code	Metric ISO thread	M
	Unified coarse (UNC) thread	U
* Material code	Carbon Steel, zinc/nickel-plated	W3
	Stainless Steel V2A	
	1.4301 / 1.4305 (AISI 304 / 303)	W4
	Stainless Steel V4A	
	1.4401 / 1.4571 (AISI 316 / 316 Ti)	W5