


## DKJ 90° (J.I.C.) Long Drop (verlängertes Schenkelmaß)

### DKJ 90° (J.I.C.) Long Drop



#### mit verlängertem Schenkelmaß

Amerikanisches Normgewinde UNF-UN

**Abdichtung:** Dichtkegelanschluss mit 74° Innenkonus

#### with extended side dimensions


American standard thread UNF-UN

**Sealing:** cone connection with 74° inner cone

PN (bar)	Dash	DN	Inch	Gewinde (G) Thread (G)	H (mm)	K (mm)	L (mm)	SW (mm) AF (mm)	Art.-Nr. Item-No.
415	-03	5	3/16"	7/16"-20 UNF	21	46	46	14	424 81 05 41
400	-04	6	1/4"	7/16"-20 UNF	25,5	46	53,5	14	424 81 06 41
400	-04	6	1/4"	1/2"-20 UNF	25,5	46	53,5	17	424 81 06 42
400	-04	6	1/4"	9/16"-18 UNF	25,5	54	53,5	19	424 81 06 43
350	-05	8	5/16"	1/2"-20 UNF	28	46	56	17	424 81 08 42
350	-05	8	5/16"	9/16"-18 UNF	28	54	56	19	424 81 08 43
350	-06	10	3/8"	9/16"-18 UNF	30	54	61,5	19	424 81 10 43
330	-06	10	3/8"	3/4"-16 UNF	31	64	61,5	22	424 81 10 44
310	-08	12	1/2"	3/4"-16 UNF	37	64	71	22	424 81 12 44
280	-08	12	1/2"	7/8"-14 UNF	38	70	71	27	424 81 12 45
250	-10	16	5/8"	7/8"-14 UNF	43	70	81	27	424 81 16 45
250	-10	16	5/8"	1 1/16"-12 UN	45	96	81	32	424 81 16 46
240	-12	19	3/4"	1 1/16"-12 UN	55	96	95	32	424 81 20 46
215	-12	19	3/4"	1 3/16"-12 UN	55	96	95	36	424 81 20 95
215	-12	19	3/4"	1 5/16"-12 UN	55	114	95	38	424 81 20 47
210	-16	25	1"	1 5/16"-12 UN	71	114	122	38	424 81 25 47

## DKJ 90° (J.I.C.) mit langer Mutter

### DKJ 90° (J.I.C.) with long nut



Amerikanisches Normgewinde UNF-UN

**Abdichtung:** Dichtkegelanschluss mit 74° Innenkonus, lange Überwurfmutter

American standard thread UNF-UN

**Sealing:** cone connection with 74° inner cone, long union nut

PN (bar)	Dash	DN	Inch	Gewinde (G) Thread (G)	H (mm)	K (mm)	L (mm)	SW (mm) AF (mm)	Art.-Nr. Item-No.
350	-08	12	1/2"	7/8"-14 UNF	37	40	70	27	424 52 62 45
350	-10	16	5/8"	7/8"-14 UNF	45	45	81	27	424 52 66 45
350	-10	16	5/8"	1 1/16"-12 UN	45	47	81	32	424 52 66 46
350	-12	19	3/4"	1 1/16"-12 UN	55	53	95	32	424 52 70 46
280	-12	19	3/4"	1 3/16"-12 UN	55	54	95	36	424 52 70 95
280	-12	19	3/4"	1 5/16"-12 UN	55	56	95	41	424 52 70 47
280	-16	25	1"	1 5/16"-12 UN	71	70	122	41	424 52 75 47
280	-16	25	1"	1 5/8"-12 UN	71	70	122	50	424 52 75 48
210	-20	31	1 1/4"	1 5/8"-12 UN	86	82	143	50	424 52 82 48
185	-24	38	1 1/2"	1 7/8"-12 UN	102	96	167	60	424 52 90 49
175	-32	51	2"	2 1/2"-12 UN	137	134	207	75	424 52 91 50