

W4




Stainless Steel Cable Tie

The self-locking mechanism of the cable tie incorporates a stainless-steel ball-bearing making it extremely secure once fastened. Due to its design, the stainless-steel cable tie is tamper-proof once it has been mounted.

Two different bandwidths are available, meaning that you can clamp up to 114kg, and in applications up to 300mm in diameter.

Assembly is carried out using a tool which tightens the tie to its limit and then cuts off the remaining material at the base of the housing, leaving no extra material protruding.

Application Ø							
mm	Part n°	Width a	Maximum diameter	Length L	Strength (Kg.)	Box Quantity (MOQ)	Outer Packing
4,50 x 33	0300200-1	4,45	33	130	46	100	8.000
4,50 x 50	0300200-2	4,45	50	200	46	100	6.000
4,50 x 76	0300200-3	4,45	76	300	46	100	5.000
4,50 x 102	0300200-4	4,45	102	370	46	100	4.000
4,50 x 156	0300200-5	4,45	156	520	46	100	4.500
4,50 x 207	0300200-6	4,45	207	680	46	100	2.000
4,50 x 245	0300200-7	4,45	245	840	46	100	1.000
7,94 x 50	0300200-8	7,96	50	200	114	100	4.500
7,94 x 76	0300200-9	7,96	76	300	114	100	4.000
7,94 x 102	0300201-0	7,96	102	370	114	100	3.000
7,94 x 135	0300201-1	7,96	135	450	114	100	2.000
7,94 x 150	0300201-2	7,96	150	500	114	100	2.000
7,94 x 207	0300201-3	7,96	207	680	114	100	2.000
7,94 x 312	0300201-4	7,96	312	1020	114	100	500

	TECHNICAL INFORMATION	
	MATERIAL	STAINLESS STEEL AISI- 304
	FINISH	STAINLESS STEEL
	CORROSION RESISTANCE	400 HOURS SALT SPRAY (ASTM B-117)

