


SFL 67,5°
SFL 67,5°

Leichte Baureihe 3000 PSI

Light duty 3000 PSI

PN (bar)	Dash	DN	Inch	Flansch Flange	Ø (mm)	H (mm)	K (mm)	L (mm)	Art.-Nr. Item-No.
350	-08	12	1/2"	1/2"	30,2	51	30	84	424 71 67 12
350	-08	12	1/2"	3/4"	38,1	54	36	87	424 71 67 19
350	-12	19	3/4"	3/4"	38,1	68	38	108	424 71 67 20
350	-12	19	3/4"	1"	44,5	69	41	109	424 71 67 21
280	-16	25	1"	1"	44,5	91	44	142	424 71 67 25
280	-16	25	1"	1 1/4"	50,8	91	44	142	424 71 67 31
210	-20	31	1 1/4"	1 1/4"	50,8	109	51	167	424 71 67 32
210	-20	31	1 1/4"	1 1/2"	60,3	109	51	167	424 71 67 39
185	-24	38	1 1/2"	1 1/2"	60,3	129	59	194	424 71 67 40



SFL 90°
SFL 90°

Leichte Baureihe 3000 PSI

Light duty 3000 PSI

PN (bar)	Dash	DN	Inch	Flansch Flange	Ø (mm)	H (mm)	K (mm)	L (mm)	Zusatz Add on	Art.-Nr. Item-No.
350	-06	10	3/8"	1/2"	30,2	41,5	40	72	-	424 72 10 12
350	-08	12	1/2"	1/2"	30,2	41	42	74	-	424 72 12 12
350	-08	12	1/2"	5/8"	34	41	44	74	Komatsu	424 86 12 16
350	-08	12	1/2"	3/4"	38,1	41	47	74	-	424 72 12 20
350	-08	12	1/2"	1"	44,5	44,3	51	74	-	424 72 12 25
350	-10	16	5/8"	1/2"	30,2	49	46	85	-	424 72 16 12
350	-10	16	5/8"	5/8"	34	49	49	85	Komatsu	424 86 16 16
350	-10	16	5/8"	3/4"	38,1	49	52	85	-	424 72 16 20
350	-10	16	5/8"	1"	44,5	49	54	89	-	424 72 16 25
350	-12	19	3/4"	1/2"	30,2	58	51	99	-	424 72 20 12
350	-12	19	3/4"	5/8"	34	50	54	91	Komatsu	424 86 20 16
350	-12	19	3/4"	3/4"	38,1	58	57	99	-	424 72 20 20
350	-12	19	3/4"	1"	44,5	58	62	99	-	424 72 20 25
280	-16	25	1"	3/4"	38,1	74	69	129	-	424 72 25 20
280	-16	25	1"	1"	44,5	74	69	129	-	424 72 25 25
280	-16	25	1"	1 1/4"	50,8	74	70	129	-	424 72 25 32
210	-20	31	1 1/4"	1"	44,5	92	78	153	-	424 72 32 25
210	-20	31	1 1/4"	1 1/4"	50,8	92	87	153	-	424 72 32 32
210	-20	31	1 1/4"	1 1/2"	60,3	92	88	153	-	424 72 32 40
185	-24	38	1 1/2"	1 1/2"	60,3	108	101	179	-	424 72 40 40
185	-24	38	1 1/2"	2"	71,4	108	104	179	-	424 72 40 50
170	-32	51	2"	1 1/2"	60,3	103	128	179	-	424 72 50 40
170	-32	51	2"	2"	71,4	142	134	218	-	424 72 50 50
170	-32	51	2"	2 1/2"	84,1	142	120	218	-	424 72 50 60
69	-40	63	2 1/2"	2 1/2"	84,1	85	95	158	-	424 72 63 63
50	-48	76	3"	3"	101,6	95	103	165	-	424 72 76 76

