


INDUSTRIAL HOSE

WATER & AIR // MULTIPURPOSE


LOCK-ON PLUS



mm	"	mm	MPa	MPa	mm	mm/Hg	kg/100m	REF.
6	1/4	11.9	2.1	8.4	45	710	13	LOLA+04
10	3/8	15.9	2.1	8.4	75	710	16	LOLA+06
13	1/2	19.6	2.1	8.4	80	710	23	LOLA+08
16	5/8	23.9	2.1	8.4	115	710	30	LOLA+10
19	3/4	26.9	2.1	8.4	135	380	36	LOLA+12
6	1/4	11.9	2.1	8.4	45	710	13	LOLB+04
10	3/8	15.9	2.1	8.4	75	710	16	LOLB+06
13	1/2	19.6	2.1	8.4	80	710	23	LOLB+08
16	5/8	23.9	2.1	8.4	115	710	30	LOLB+10
19	3/4	26.9	2.1	8.4	135	380	36	LOLB+12
6	1/4	11.9	2.1	8.4	45	710	13	LOLC+04
10	3/8	15.9	2.1	8.4	75	710	16	LOLC+06
13	1/2	19.6	2.1	8.4	80	710	23	LOLC+08
16	5/8	23.9	2.1	8.4	115	710	30	LOLC+10
19	3/4	26.9	2.1	8.4	135	380	36	LOLC+12
6	1/4	11.9	2.1	8.4	45	710	13	LOLG+04
10	3/8	15.9	2.1	8.4	75	710	16	LOLG+06
13	1/2	19.6	2.1	8.4	80	710	23	LOLG+08
16	5/8	23.9	2.1	8.4	115	710	30	LOLG+10
19	3/4	26.9	2.1	8.4	135	380	36	LOLG+12
6	1/4	11.9	2.1	8.4	45	710	13	LOLR+04
10	3/8	15.9	2.1	8.4	75	710	16	LOLR+06
13	1/2	19.6	2.1	8.4	80	710	23	LOLR+08
16	5/8	23.9	2.1	8.4	115	710	30	LOLR+10
19	3/4	26.9	2.1	8.4	135	380	36	LOLR+12

INDUSTRIAL HOSE WATER & AIR // MULTIPURPOSE

LOCK-ON PLUS



RECOMMENDED FOR	Petroleum-based hydraulic oils, antifreeze solutions, water, hot lubricating oils and air. Suitable for low-pressure cleaning and pneumatic systems, return lines and low pressure lines. Lock-On hose and couplings are not recommended for pressure surge applications or critical applications.
TUBE	NBR (Nitrile) based.
REINFORCEMENT	One fibre braid.
COVER	NBR/PVC based.
TEMPERATURE RANGE	-40°C to +100°C constant and +121°C intermittent. For water emulsions, etc. see Temperature Limits Table.
STANDARDS	Gates proprietary.
COUPLINGS	Lock-On Plus reusable couplings.
CHARACTERISTICS/BENEFITS	Available in 5 colours for easy colour coding. Easy to assemble.

A = black
R = red
B = blue
C = grey
G = green