

Festkupplungen mit Innengewinde Adapters with female thread




Dichtung: Nitril-Kautschuk schwarz / weiß
Viton Dichtung bei V4A

Seal: Nitrile rubber black / white
Fluoro rubber - Stainless steel

Gewinde - thread: **DIN ISO 228**

Aluminium light alloy	Messing copper alloy	Edelstahl stainless steel
--------------------------	-------------------------	------------------------------



Storz Size	KA (mm) Lug	Innengewinde Female thread	Weight (kg)	Bemerkung Remark	Ident-No.	Euro
25-D	31	1/2 "	0,08		21-031050-10	
		1/2 "	0,25		21-031050-30	
		1/2 "	0,27		21-031050-43	
		3/4 "	0,08		21-031075-10	
		3/4 "	0,23		21-031075-30	
		3/4 "	0,25		21-031075-43	
		1 "	0,08	DIN 14 306	21-031100-10	
		1 "	0,23		21-031100-30	
		1 "	0,21		21-031100-43	
		1 1/4 "	0,09		21-031125-10	
32	44	1 "	0,16		21-044100-10	
		1 "	0,45		21-044100-30	
		1 1/4 "	0,14		21-044125-10	
		1 1/4 "	0,39		21-044125-30	
38	51	1 "	0,15		21-051100-10	
		1 "	0,44		21-051100-30	
		1 1/4 "	0,17		21-051125-10	
		1 1/4 "	0,51		21-051125-30	
		1 1/4 "	0,52		21-051125-43	
		1 1/2 "	0,15		21-051150-10	
		1 1/2 "	0,44		21-051150-30	
		1 1/2 "	0,47		21-051150-43	
		2 "	0,18		21-051200-10	
45	59	1 1/2 "	0,25		21-059150-15	
		2 "	0,24		21-059200-15	
52-C	66	3/4 "	0,29		21-066075-15	
		3/4 "	0,88		21-066075-43	
		1 "	0,28		21-066100-15	
		1 "	1,11		21-066100-30	
		1 "	1,08		21-066100-43	

Festkupplungen mit Innengewinde
Adapters with female thread



Storz Size	KA (mm) Lug	Innengewinde Female thread	Weight (kg)	Bemerkung Remark	Ident-No.	Euro
52-C	66	1 1/4 "	0,30		21-066125-15	
		1 1/4 "	0,29	gegossen / cast *	21-066125-21	
		1 1/4 "	0,91		21-066125-30	
		1 1/4 "	1,02		21-066125-43	
		1 1/2 "	0,28		21-066150-15	
		1 1/2 "	0,26	gegossen / cast *	21-066150-21	
		1 1/2 "	1,00		21-066150-30	
		1 1/2 "	0,98		21-066150-43	
		1 3/4 "	0,24		21-066175-15	
		2 "	0,28	DIN 14 307	21-066200-15	
		2 "	0,24	gegossen / cast *	21-066200-21	
		2 "	0,80	DIN 86 204	21-066200-35	
		2 "	0,77		21-066200-43	
		2 1/2 "	0,28		21-066250-15	
		2 1/2 "	0,90		21-066250-30	
		2 1/2 "	1,54	mit V4A - Red.stück	21-066250-43	
65	81	1 "	0,53		21-081100-10	
		1 1/4 "	0,50		21-081125-10	
		1 1/2 "	0,45		21-081150-10	
		2 "	0,38		21-081200-10	
		2 "	1,47		21-081200-30	
		2 "	1,31		21-081200-43	
		2 1/2 "	0,38		21-081250-10	
		2 1/2 "	1,12		21-081250-30	
		2 1/2 "	1,02		21-081250-43	
		3 "	0,41		21-081300-10	
		3 "	1,20		21-081300-30	
75-B	89	2 "	0,43		21-089200-15	
		2 "	1,65		21-089200-30	
		2 "	1,50		21-089200-43	
		2 1/2 "	0,42	DIN 14 308	21-089250-15	
		2 1/2 "	0,39	gegossen / cast *	21-089250-21	
		2 1/2 "	1,26	DIN 86 205	21-089250-30	
		2 1/2 "	1,51		21-089250-43	

Festkupplungen mit Innengewinde
Adapters with female thread



Storz Size	KA (mm) Lug	Innengewinde Female thread	Weight (kg)	Bemerkung Remark	Ident-No.	Euro
75-B	89	3 "	0,42		21-089300-15	
		3 "	0,43	gegossen / cast *	21-089300-21	
		3 "	0,49	Stahlkern inside steel	21-089300-50	
		3 "	1,50		21-089300-30	
		3 "	1,26		21-089300-43	
90	105	3 "	0,60		21-105300-10	
100	115	4 "	0,85		21-115400-10	
		4 "	1,96		21-115400-30	
		4 "	2,22		21-115400-43	
110-A	133	3 "	1,43	mit Red.stück	21-133300-10	
		4 "	1,09		21-133400-10	
		4 "	0,92	gegossen / cast *	21-133400-21	
		4 "	1,27	Stahlkern inside steel	21-133400-50	
		4 "	1,25	Edelstahlkern inside stainless steel	21-133400-70	
		4 "	3,77		21-133400-30	
		4 "	3,50		21-133400-43	
		4½ "	1,12	DIN 14 309	21-133450-10	
		4½ "	3,40		21-133450-30	
		4½ "	3,20		21-133450-43	
		5 "	1,39	mit Muffe	21-133500-10	
125	148	4 "	1,68		21-148400-10	
		5 "	1,38		21-148500-10	
		5 "	2,68		21-148500-30	
		5 "	3,55		21-148500-43	
150	160	6 "	1,82		21-160600-10	
		6 "	5,63		21-160600-30	
		6 "	5,30		21-160600-43	
165	188	6 "	2,16	max. PN 10 bar	21-188600-10	
205	220	8 "	3,48	max. PN 10 bar	21-220800-10	
250	278	10 "	5,35	max. PN 10 bar	21-278000-10	

* Industriekupplung PN 6 (siehe Seite 61)

Industrial coupling PN 6 (see page 61)