

COUPLINGS


BANJO COUPLING

SB BANJO COUPLING CHOKE-FREE

THE WORLD OF TUBE FITTINGS

SB BANJO COUPLING CHOKE-FREE BSP

BSP parallel.



description	pipe OD	PB series	S ₁	S ₂	S ₃	L ₂	l ₂	l ₃	L ₃	d ₃	i	G	kg % pc
DS-SB 6-RL	6	L 250	14	18	6	27	12.5	12.0	24	14	8	G 1/8" A	5.9
DS-SB 8-RL	8	L 250	17	22	8	29	14.5	16.0	30	18	12	G 1/4" A	10.5
DS-SB 10-RL	10	L 250	19	22	8	30	15.5	16.0	30	18	12	G 1/4" A	11.3
DS-SB 12-RL	12	L 250	22	27	10	33	18.0	18.0	37	22	12	G 3/8" A	18.0
DS-SB 15-RL	15	L 250	27	32	12	37	22.0	21.0	42	26	14	G 1/2" A	24.7
DS-SB 18-RL	18	L 100	32	36	12	38	21.5	23.0	46	26	14	G 1/2" A	26.9
DS-SB 22-RL	22	L 100	36	46	17	45	28.5	28.0	58	32	16	G 3/4" A	54.6
DS-SB 28-RL	28	L 100	41	50	22	48	31.5	30.5	64	39	18	G 1" A	83.0
DS-SB 35-RL	35	L 100	50	60	27	57	35.5	36.0	76	49	20	G 1 1/4" A	117.3
DS-SB 42-RL	42	L 100	60	70	32	63	40.0	41.0	85	55	22	G 1 1/2" A	224.4
DS-SB 6-RS	6	S 400*	17	22	8	31	16.5	16.0	30	18	12	G 1/4" A	10.9
DS-SB 8-RS	8	S 400*	19	22	8	31	16.5	16.0	30	18	12	G 1/4" A	11.4
DS-SB 10-RS	10	S 400*	22	27	10	35	18.5	18.0	37	22	12	G 3/8" A	19.0
DS-SB 12-RS	12	S 400*	24	27	10	35	18.5	18.0	37	22	12	G 3/8" A	19.6
DS-SB 14-RS	14	S 400*	27	32	12	41	23.0	21.0	42	26	14	G 1/2" A	29.7
DS-SB 16-RS	16	S 400*	30	36	12	41	22.5	23.0	46	26	14	G 1/2" A	30.7
DS-SB 20-RS	20	S 400*	36	46	17	49	27.5	28.0	58	32	16	G 3/4" A	75.3
DS-SB 25-RS	25	S 250*	46	50	22	55	31.0	30.5	64	39	18	G 1" A	101.9
DS-SB 30-RS	30	S 250*	50	60	27	63	36.5	36.0	76	49	20	G 1 1/4" A	158.0
DS-SB 38-RS	38	S 250*	60	70	32	72	41.0	41.0	85	55	22	G 1 1/2" A	243.2

L₂ = approximate length with nut tightened

* Security factor minimum 1.6

Please see "Engineering and technical data - Selecting the correct tube fitting" for more information on pressure.