



-5°C ÷ +70°C



10 Bar



Compressed air, lubricated compressed air, gas and fluids suitable with construction materials



Parallel gas BSPP ISO 228 from G1/8" to G1/2"
Taper gas ISO 7 from R1/8" to R1/2"

OPERATION
90° lever rotation

- Body:** Brass CW 617N
- Retainer:** Brass CW 614N
- Stem:** Brass CW 614N
- Ball:** Brass CW 614N nickel plated
- Ball gasket:** PTFE (Teflon)
- Screw:** Steel
- Stem sealing O'ring:** NBR 70 on demand viton
- Lever:** Nylon 6.6
- Button:** Nylon 6.6




Products in compliance with the directive 2002/95/EC

RoHS2

Products in compliance with the directive 2011/65/EU

Micro ball valve F/F black lever


9142



CODE	T1	T2	D	E	C	L1	L2	L3	GR.
9142TR18	G1/8"	G1/8"	6	24	23	34	8,0	8,0	35,0
9142TR14	G1/4"	G1/4"	6	24	23	38	9,5	9,5	39,0
9142TR38	G3/8"	G3/8"	8	24	24	43	10,5	10,5	55,0
9142TR12	G1/2"	G1/2"	10	34	27	49	12,0	12,0	93,0

Micro ball valve M/F black lever

9162




CODE	T1	T2	D	E	C	L1	L2	L3	GR.
9162TR18	R1/8"	G1/8"	6	24	23	34	8,0	7,5	32,0
9162TR14	R1/4"	G1/4"	6	24	23	39	9,5	11,0	36,0
9162TR38	R3/8"	G3/8"	8	24	24	43	10,5	11,5	51,0
9162TR12	R1/2"	G1/2"	10	24	27	50	12,0	15,0	87,0



9168

Micro ball valve M with ogive connection for copper or aluminium tube black lever



CODE	T	TUBE	R	E	C	L1	L2	GR.
9168TR186	R1/8"	6	6	24	23	41	7,5	38,0

