

Water max 130°C 100 bar Hygienic hose

For the SWIVELLING version add the suffix "/SO" at the P/N, except for the 560 series.
For example: 302/40/SO

FIXED S. STEEL AISI 304



Supplied with:

- hose in synthetic rubber with blue hygienic covering with galvanized steel coupling
- AISI 304 stainless steel swivel joint
- Viton® seals
- central shaft in stainless steel AISI 304
- inlet hose 0,6 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	Hygienic hose supplied	Connection	
			Inlet	Outlet
S. 300	302/40	without hose*	F 1/2"G	F 3/8"-1/2"G
	303/21	8m 1/2" (964/8)	F 1/2"G	M 1/2"G
	303/22	12m 3/8" (954/13)	F 1/2"G	M 3/8"G
S. 350	352/40	without hose*	F 1/2"G	F 3/8"- 1/2"G
	353/22	12m 3/8" (954/13)	F 1/2"G	M 3/8"G
S. 430	434/20	without hose*	F 1/2"G	F 1/2"G
	433/21	10m 1/2" (964/11)	F 1/2"G	M 1/2"G
	433/22	15m 1/2" (964/15)	F 1/2"G	M 1/2"G
S. 4430 ABS	4434/20	without hose*	F 1/2"G	F 1/2"G
	4433/21	10m 1/2" (964/11)	F 1/2"G	M 1/2"G
	4433/22	15m 1/2" (964/15)	F 1/2"G	M 1/2"G
S. 530	534/20	without hose*	F 1/2"G	F 1/2"G
	533/22	25m 1/2" (964/25)	F 1/2"G	M 1/2"G
S. 540	544/20	without hose*	F 1"G	F 1"G
	543/22	20m 3/4" (974/20)	F 1"G	M 3/4"G
S. 560	564/20	without hose*	F 1"G	F 1"G
	563/21	30m 3/4" (974/30)	F 1"G	M 3/4"G
	563/23	40m 3/4" (974/40)	F 1"G	M 3/4"G
	563/24**	20m 1" (984/20)	F 1"G	M 1"G
	563/25**	30m 1" (984/30)	F 1"G	M 1"G

Rubber handles, mounted on hose terminal part, are available for all the above series. For more information look at page 50.

** Work max pressure 50 bar, hose max pressure 88 bar

* For the version without hose the maximum working pressure is 150 bar



Atex 94/9

- › II 3GD c X (only for series 300-350-4430 ABS)
- › IIB 2GD c T4 T135°C X