



# DM 80 Series - Metric Tube



**\*MATERIAL CODE:**  
**K = STAINLESS STEEL**  
**G = CARBON STEEL**  
**B = COPPER NICKEL 70/30**

**ORDER EXAMPLE:**  
**DM80002G06**

## Coupling with Inner Stop, Metric - DM80002

| Size<br>OD (mm) | Part Number | Dimensions - mm (Inch) |              |                      | *Weight K & G<br>kg (lbs) |
|-----------------|-------------|------------------------|--------------|----------------------|---------------------------|
|                 |             | A                      | B            | C<br>Insertion Depth |                           |
| 6               | DM80002*06  | 34.29 (1.35)           | 9.80 (0.39)  | 16.51 (0.65)         | 0.01 (0.02)               |
| 8               | DM80002*08  | 39.88 (1.57)           | 12.19 (0.48) | 19.30 (0.76)         | 0.01 (0.03)               |
| 10              | DM80002*10  | 49.53 (1.95)           | 15.09 (0.59) | 24.13 (0.95)         | 0.06 (0.03)               |
| 12              | DM80002*12  | 55.37 (2.18)           | 18.59 (0.73) | 26.92 (1.06)         | 0.05 (0.10)               |
| 15              | DM80002*15  | 65.28 (2.57)           | 23.70 (0.93) | 32.00 (1.26)         | 0.10 (0.23)               |
| 16              | DM80002*16  | 65.28 (2.57)           | 23.70 (0.93) | 32.00 (1.26)         | 0.09 (0.20)               |
| 18              | DM80002*18  | 71.12 (2.80)           | 25.15 (0.99) | 35.05 (1.38)         | 0.10 (0.22)               |
| 20              | DM80002*20  | 75.44 (2.97)           | 28.70 (1.13) | 37.08 (1.46)         | 0.15 (0.32)               |
| 22              | DM80002*22  | 77.47 (3.05)           | 30.48 (1.20) | 38.10 (1.50)         | 0.15 (0.33)               |
| 25              | DM80002*25  | 85.34 (3.36)           | 35.31 (1.39) | 41.91 (1.65)         | 0.24 (0.54)               |
| 28              | DM80002*28  | 90.17 (3.55)           | 37.59 (1.48) | 44.45 (1.75)         | 0.25 (0.55)               |
| 30              | DM80002*30  | 95.25 (3.75)           | 41.91 (1.65) | 46.99 (1.85)         | 0.39 (0.85)               |
| 35              | DM80002*35  | 102.87 (4.05)          | 46.23 (1.82) | 50.80 (2.00)         | 0.41 (0.91)               |
| 38              | DM80002*38  | 110.24 (4.34)          | 52.07 (2.05) | 54.61 (2.15)         | 0.71 (1.57)               |
| 42              | DM20002*20  | 121.92 (4.80)          | 57.40 (2.26) | 60.45 (2.38)         | 0.89 (1.96)               |
| 50              | DM80002*50  | 128.27 (5.05)          | 65.53 (2.58) | 63.50 (2.50)         | 0.89 (1.96)               |
| **60K           | DM20002K32  | 179.07 (7.05)          | 77.22 (3.04) | 88.90 (3.50)         | 2.00 (4.40)               |
| 60G             | DM80002G60  | 179.07 (7.05)          | 77.22 (3.04) | 88.90 (3.50)         | 2.00 (4.40)               |

\*\*2" DM 20 Series Stainless Steel fittings are also used for 60mm Stainless Steel applications.