



Mutterteil Typ C - MIL A-A-59326A - Stutzen für Schelleneinband

Sicherheitsverschluss System Self-Lock mit NBR Dichtung

Female coupler type C - MIL A-A-59326A with grooved hose-shank - System Self-Lock - NBR gasket

Coupleur type C douille annelée sans collerette - MIL A-A-59326A - Système Self-Lock - Joint NBR

Camlock tipo C: acople hembra - espiga para manguera - Anillas de seguridad - Junta NBR

Kobieta Typ C - niazdo z karbowaną końcówką do węża do mocowania opaskami - System samoblokujący - NBR Uszczelka

Camlock femmina tipo C - MIL A-A-59326A con portagomma - Anello di sicurezza autobloccante - Guarnizione NBR

Part-No.	Material	WP	Dimension	Shank	Price
C200AL-SL	Aluminum	10 bar	DN50	51mm	
C300AL-SL	Aluminum	10 bar	DN80	76mm	
C400AL-SL	Aluminum	7 bar	DN100	103mm	



Mutterteil Typ D - MIL A-A-59326A mit BSPP Innengewinde

mit NBR Dichtung

Female coupler type D - MIL A-A-59326A with female BSPP thread - NBR gasket

Coupleur type D taraudé femelle BSPP - MIL A-A-59326A - Joint NBR

Camlock tipo D: acople hembra - rosca hembra BSPP - Junta NBR

Kobieta Typ D - MIL A-A-59326A - Gniazdo z gwintem wewnętrznym BSPP - NBR Uszczelka

Camlock tipo D: versione femmina filettato femmina BSPP - Guarnizione NBR

Part-No.	Material	WP	Dimension	Thread	Price
D050AL	Aluminum	10 bar	DN15	1/2"	
D075AL	Aluminum	10 bar	DN20	3/4"	
D100AL	Aluminum	10 bar	DN25	1"	
D125AL	Aluminum	10 bar	DN32	1 1/4"	
D150AL	Aluminum	10 bar	DN40	1 1/2"	
D200AL	Aluminum	10 bar	DN50	2"	
D250AL	Aluminum	10 bar	DN65	2 1/2"	
D300AL	Aluminum	10 bar	DN80	3"	
D400AL	Aluminum	7 bar	DN100	4"	
D500AL	Aluminum	5 bar	DN125	5"	
D600AL	Aluminum	5 bar	DN150	6"	
D800AL	Aluminum	4 bar	DN200	8"	

