

Cleaning Service

EHF003

Dairy Washdown



Application

- For cleaning in food processing plant

Markets

- Food processing

Construction

Tube Oil and steam resistant EPDM rubber
Meets FDA & European requirements

Reinforcement

High-tensile synthetic textile

Cover Oil, heat, abrasion, ozone and weather resistant EPDM rubber

Color Blue (BU), Black (BK), Red (RD)

Certifications

Regulation EC 1935/2004
Regulation EC 2023/2006
FDA regulation CFR Title No.21 art 177.2600

Operating temperature

-40°C to +165°C, (-40°F to +329°F)

Packaging

100 ft
Coil on Pallet

Order Fulfillment

Made to Order

Number	Hose I.D.		Hose O.D.		Max Operating Pressure Hot Water +80°C		Max Operating Pressure Steam to +165°C		Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHF003-06BU	9.5	0.38	20.0	0.79	20.0	300	7.0	100	70.0	1015	0.30	0.20	30.5	100
EHF003-08BU	12.7	0.50	24.0	0.94	20.0	300	7.0	100	70.0	1015	0.41	0.28	30.5	100
EHF003-10BU	15.9	0.62	28.0	1.10	20.0	300	7.0	100	70.0	1015	0.51	0.34	30.5	100
EHF003-12BU	19.0	0.75	31.0	1.22	20.0	300	7.0	100	70.0	1015	0.60	0.40	30.5	100
EHF003-16BU	25.4	1.00	37.0	1.46	20.0	300	7.0	100	70.0	1015	0.68	0.46	30.5	100
EHF003-20BU	31.8	1.25	46.0	1.81	20.0	300	7.0	100	70.0	1015	1.07	0.72	30.5	100
EHF003-24BU	38.1	1.50	53.0	2.09	20.0	300	7.0	100	70.0	1015	1.34	0.90	30.5	100
EHF003-28BU	44.5	1.75	60.0	2.36	20.0	300	7.0	100	70.0	1015	1.57	1.06	30.5	100
EHF003-32BU	50.8	2.00	67.5	2.66	20.0	300	7.0	100	70.0	1015	1.97	1.32	30.5	100
EHF003-40BU	63.5	2.50	81.0	3.19	20.0	300	7.0	100	70.0	1015	2.50	1.68	30.5	100
EHF003-48BU	76.2	3.00	98.0	3.86	20.0	300	7.0	100	70.0	1015	3.66	2.46	30.5	100
EHF003-64BU	101.6	4.00	124.0	4.88	20.0	300	7.0	100	70.0	1015	4.83	3.25	30.5	100

Type of couplings

- Barbed inserts

Contact coupling manufacturer for attachment procedure and other coupling recommendations