

For the SWIVELLING version add the suffix "/SO" at the P/N, except for the 560 series.
For example:
300/40/SO

FIXED PAINTED STEEL

FIXED S. STEEL AISI 304

Supplied with:

- hose in black synthetic rubber with galvanized steel coupling
- swivel joint in galvanized steel or s. steel AISI 304
- Polyurethane seals
- central shaft in galvanized steel or stainless steel AISI 304
- inlet hose 0,6 m to connect the hose reel to the system (standard on the versions with hose)



		P/N	P/N	Hose supplied	Connection	
					Inlet	Outlet
150 bar	S. 300	300/40	302/40	without hose	F 1/2"G	F 3/8" - 1/2"G
		300/41	302/41	8m 1/2" (963/8)	F 1/2"G	M 1/2"G
		300/42	302/42	12m 3/8" (953/12)	F 1/2"G	M 1/2"G
	S. 350	350/40	352/40	without hose	F 1/2"G	F 3/8" - 1/2"G
		350/41	352/41	10m 1/2" (963/10)	F 1/2"G	M 1/2"G
		350/42	352/42	17m 3/8" (953/17)	F 1/2"G	M 1/2"G
		350/43	352/43	12m 3/8" (953/12)	F 1/2"G	M 1/2"G
	S. 430	430/40	434/20	without hose	F 1/2"G	F 1/2"G
		430/41	432/41	10m 1/2" (963/11)	F 1/2"G	M 1/2"G
		430/42	432/42	15m 1/2" (963/15)	F 1/2"G	M 1/2"G
	S. 4430 ABS	4430/40	4434/20	without hose	F 1/2"G	F 1/2"G
		4430/41	4432/41	10m 1/2" (963/11)	F 1/2"G	M 1/2"G
		4430/42	4432/42	15m 1/2" (963/15)	F 1/2"G	M 1/2"G
	S. 530	530/40	534/20	without hose	F 1/2"G	F 1/2"G
		530/41	532/41	20m 1/2" (963/20)	F 1/2"G	M 1/2"G
		530/42	532/42	25m 1/2" (963/25)	F 1/2"G	M 1/2"G
	S. 540	540/45	544/25	without hose	F 1/2"G	F 1/2"G
		540/46	542/46	30m 1/2" (963/30)	F 1/2"G	M 1/2"G
	S. 560	560/40	-	without hose	F 1"G	F 1"G
		560/46	-	without hose	F 1/2"G	F 1/2"G
560/47		-	40m 1/2" (963/40)	F 1/2"G	M 1/2"G	
560/48		-	50m 1/2" (963/50)	F 1/2"G	M 1/2"G	
560/49		-	60m 1/2" (963/60)	F 1/2"G	M 1/2"G	
100 bar	S. 430	430/415	-	without hose	F 1/2"G	M 1/2"G
		430/416	-	10m 5/8" (993/310)	F 3/4"G	M 3/4"G
		430/417	-	8m 3/4" (973/308)	F 3/4"G	M 3/4"G
	S. 4430 ABS	4430/415	-	without hose	F 1/2"G	M 1/2"G
		4430/416	-	10m 5/8" (993/310)	F 3/4"G	M 3/4"G
		4430/417	-	8m 3/4" (973/308)	F 3/4"G	M 3/4"G
	S. 530	530/415	-	without hose	F 1"G	F 1"G
		530/416	-	12m 3/4" (973/312)	F 3/4"G	M 3/4"G
	S. 540	540/40	544/20	without hose	F 1"G	F 1"G
		540/411	-	15m 3/4" (973/315)	F 3/4"G	M 3/4"G
		540/412	-	20m 3/4" (973/320)	F 3/4"G	M 3/4"G
	S. 560	-	564/20	without hose	F 1"G	F 1"G
-		564/26	without hose	F 1/2"G	F 1/2"G	
560/411		-	30m 3/4" (973/330)	F 3/4"G	M 3/4"G	
560/413		-	40m 3/4" (973/340)	F 3/4"G	M 3/4"G	
50 bar	S. 540	540/413	-	15m 1" (983/315)	F 1"G	M 1"G
		540/414	-	10m 1" (983/310)	F 1"G	M 1"G
	S. 560	560/414	-	20m 1" (983/320)	F 1"G	M 1"G
		560/415	-	30m 1" (983/330)	F 1"G	M 1"G


Atex 94/9

- ▶ II 3GD c X (only for series 300-350-4430 ABS)
- ▶ IIB 2GD c T4 T135°C X