

Description

Item No.

TG 500 One-Hand Grease Gun Kit

galvanized

Suits 400 g cartridges or 500 g bulk fill, equipped with combined air release/filling valve (for use with pail mounted filler pumps), pressure capability approx. 300 bar. New ergonomically engineered heavy-duty design, delivery rigid tube can be fitted either horizontally or vertically, thereby ensuring optimal access to even difficult to reach lubrication spots. Either without accessories or with rigid steel tube or 300 mm high pressure nylon hose PH-30C or 300 mm high pressure safety rubber hose RH-30C. Packed in sturdy display carton with user instructions and safety advise.



with rigid tube, M10x1 32 101 06

with rigid tube, R1/8" 32 101 20

with nylon hose PH-30C, M10x1 32 103 04

with nylon hose PH-30C, R1/8" 32 103 28

with safety rubber hose RH-30C, M10x1 32 102 05

with safety rubber hose RH-30C, R1/8" 32 102 29



DF - One-Hand Air-Operated Grease Gun

For use with standard grease cartridges 400 g, filler pump or bulk fill, for greases up to NLGI 2, DIN 51818. Single shot system (1 cc per stroke), pressure ratio 60:1, air pressure from 3 to max. 8 bar, maximum working pressure 480 bar (6.950 psi).

with rigid tube E4024, M10x1 34 101 55

with rigid tube E4024, R1/8" 34 100 01

with safety rubber hose RH-30C, M10x1 34 101 79

with safety rubber hose RH-30C, R1/8" 34 100 56



DFO - One Hand Air Operated Oil Gun

Technical Data see DF 500, but with oil tight inner piston. Accessory set includes hydraulic connector with backlash valve.

with rigid tube E4024, R1/8" 34 101 00

with safety rubber hose RH-30C, R1/8" 34 101 24

Pull-Off Grease Cartridges 400 g

DIN 1284

Diameter: max. 53.5 mm, Length: 235 mm
For specification of grease Multi basic EP-2M, MULTI Plus EP-2M und GRAPHITE EP-2M GR (see page 11)

MATO recommends empty cartridges of NMPB France: www.mpb-plastics.com



MULTI basic EP-2M, KP2K-30 31 000 18

MULTI PLUS EP-2M, KP2K-30 31 001 24

GRAPHITE EP-2M GR, KPF2K-30 31 002 09

