

Polyamidrohre Polyamide tubes



Temperaturbereich: -40 °C bis +90 °C
Werkstoff: Polyamid (PA12)
Norm: DIN 73378 / DIN 74324
Farbe: schwarz
Temperature range: -40 °C to +90 °C
Material: polyamide (PA12)
Norm: DIN 73378 / DIN 74324
Colour: black

Außen-Ø (mm) Outer-Ø (mm)	Wandstärke (mm) Wall thickness (mm)	Biegeradius (mm) Bending radius (mm)	DIN	Lieferlänge (m) Delivery length (m)	Betriebsdruck 20° Working pressure 20°	Art.-Nr. Item-No.
3	0,65	20	73378	100	16	672 201
4	0,65	20	73378	50	20	672 025
4	0,85	20	73378	100	24	672 012
4	1	20	74324	100	45	672 018
5	1	30	73378	100	37	672 016
6	1	30	74324	25	36	672 051
6	1	30	74324	100	36	672 001
6	1	30	74324	500	29	672 091 01
6	1	30	74324	2100	36	672 091 03
6	1,5	30	73378	25	60	672 052
6	1,5	30	73378	100	60	672 002
6	2	30	73378	100	130	672 024
8	1	40	74324	25	26	672 053
8	1	40	74324	100	26	672 003
8	1	40	74324	1300	26	672 093 01
8	1,5	40	73378	25	42	672 054
8	1,5	40	73378	100	42	672 004
9	1,5	45	74324	25	36	672 063
9	1,5	45	74324	100	36	672 013
10	1	60	74324	25	20	672 055
10	1	60	74324	100	20	672 005
10	1	60	74324	650	16	672 095 01
10	1,25	60	74324	100	21	672 017
10	1,5	70	73378	25	22	672 058
10	1,5	70	73378	100	22	672 008
11	1,5	60	74324	25	23	672 060
11	1,5	60	74324	100	23	672 010
12	1	110	73378	100	12	672 009
12	1	110	73378	650	12	672 095 03
12	1,5	60	74324	25	26	672 056
12	1,5	60	74324	100	26	672 006
12	1,5	60	74324	500	26	672 096 01
12,5	1,25	60	73378	100	16	672 021
13	1,5	100	73378	100	30	672 023
14	1,5	80	73378	100	16	672 026
14	2	75	74324	100	24	672 014
15	1,5	90	74324	25	20	672 057
15	1,5	90	74324	100	20	672 007
15	1,5	90	74324	300	20	672 097 01
16	1,5	90	73378	100	20	672 129
16	2	95	74324	100	26	672 015
18	2	100	74324	100	23	672 011
22	2	180	73378	100	13	672 019