

CTA

HY-CAP Capsules in shrink-wrapping PVC

Capsule in PVC termoretraibili



System for preventing the internal contamination of the assembled hose up to the time of assembly, equivalent and alternative to the traditional threaded plastic plug.

Sistema per prevenire la contaminazione interna del tubo flessibile assemblato fino al momento del montaggio, equivalente ed alternativo al tradizionale tappo filettato in plastica.

Features:

Environment: Reduction of plastic waste quantities.

Material: Thermoplastic polyvinyl chloride (PVC) foil leaf.

Range: Cover of all applications with only 7 capsules diameters.

Management: Controls, documenting and reordering only 7 codes.

Warehouse: No more stock of hundreds types of plugs.

Heat-shrinking times around the second.

Capsule color and logo customizable, for minimum order quantity.

Caratteristiche:

Ambiente: Riduzione dei quantitativi di smaltimento di plastica.

Materiale: Foglia termoplastica in cloruro di polivinile (PVC) rigido.

Gamma: Copertura di tutte le applicazioni con soli 7 diametri di capsule.

Gestione: Controlli, documentazione e riordino di soli 7 codici.

Magazzino: Non più stock di centinaia di tipologie di tappi.

Tempi di termoretrazione intorno al secondo.

Colore capsula e logo personalizzabili, per quantitativo minimo d'ordine.

				
Part number	Size	Roll	Hexagonal	Q.ty
		length	covered	Box
CTA2530IFS	25	30	12/22	5805
CTA2850IFS	28	50	22/24	3120
CTA3140IFS	31	40	24/27	3864
CTA3440IFS	34	40	27/30	3828
CTA3850IFS	38	50	30/32	2200
CTA4660IFS	46	60	32/41	1320
CTA5860NA	58	60	41/50	1344
CTA7050NA	70	50	50/60	750
CTA8060NA	80	60	60/70	580

HSM

Heat shrink machine

Fornello per termoretrazione



System for preventing the internal contamination of the assembled hose up to the time of assembly, equivalent and alternative to the traditional threaded plastic plug.

Sistema per prevenire la contaminazione interna del tubo flessibile assemblato fino al momento del montaggio, equivalente ed alternativo al tradizionale tappo filettato in plastica.

Features:

230 V (1000 W)

Material: Stainless steel

Versions: Table mounted (HSMB1)

Manual, with or without base support stand (bss) (HSM A1 and HSM A2)

Caratteristiche:

230 V (1000 W)

Materiale: Acciaio inox

Versions: Da banco (HSMB1)

Manuale, con o senza supporto (HSM A1 e HSM A2)

Part number	Version	Weight Kg	Dimensions (mm)	
			A X B	h
HSM A1	Manual, without bss	1.5	240x100	240
HSM A2	Manual, with bss	2.0	240x180	320
HSMB1	Table mounted	3.0	480x150	220