

AUßENGEWINDE - SCHLAUCHNIPPEL

Type 8077

NPTF, mit 60° Innen-Konus

NIPPLE WITH OUTSIDE THREAD

NPTF, with 60° inner cone



DN (NW)	für Schlauch-Innen-Ø for hose inside Ø mm	SW mm	Gewinde thread	L 1 mm	L 2 mm	Bestell-Nr. part-no
3/4	5 - 6	13	1/8" - 27 NPTF	17	10	8077.0304
6	7 - 8	17	1/4" - 18 NPTF	21	14	8077.0600
6/8	9 - 10	17	1/4" - 18 NPTF	21	14	8077.0608
8	9 - 10	19	3/8" - 18 NPTF	21	14	8077.0800
8/10	11 - 12	19	3/8" - 18 NPTF	21	14	8077.0810
13	14 - 15	24	1/2" - 18 NPTF	27	19	8077.1300
20	21 - 22	30	3/4" - 14 NPTF	29	19	8077.2000
20/16	17 - 18	30	3/4" - 14 NPTF	29	19	8077.2016
25/20	21 - 22	36	1- 11 1/2" NPTF	36	24	8077.2520

ROHR - SCHLAUCHNIPPEL

Type 8061

leichte Baureihe

TUBE NIPPLE

light type



DN (NW)	Rohr-Außen-Ø pipe outside-Ø D mm	für Schlauch-Innen-Ø for hose inside Ø mm	L mm	Bestell-Nr. part-no
2	4	3 - 4	30	8061.0200
3	5	4 - 5	30	8061.0300
4	6	5 - 6	30	8061.0400
6	8	7 - 8	30	8061.0600
8	10	9 - 10	30	8061.0800
10	12	11 - 12	30	8061.1000
13	15	14 - 15	30	8061.1300
16	18	17 - 18	30	8061.1600
20	22	21 - 22	30	8061.2000
25	28	24 - 25	36	8061.2500

Typen 8040.90, 8044.90, 8061, 8081.90 ab DN 13 mit profiliertem Schlauchsitz.

Types 8040.90, 8044.90, 8061, 8081.90 from DN 13 with profiled hose nipple.

