

INTERPUMP Jet 2SC

APPLICATIONS :



APPLICABLE SPECIFICATIONS

EN 857 2SC - ISO 7751

TFN002K TFB002K



Dimensions according to EN 857 2SC. NO-SKIVE flexible line. Safety factor exceeding ISO 7751. Product designed for pressure wash applications. Any different use may reduce service life.

Inner tube: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Coverage: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluids: Water, water-soap based, glycol-water based.

working temperature: from -40 to +135°C (intermittent 155°C).

Product number	ID		Dimension dash size	OD	Max WP		Min BP		Min BR		Weight (approx)		Ferrule	Color Coverage
	in	mm			bar	psi	bar	psi	mm	inch	kg/m	lb/ft		
TFN002KN04	1/4"	6.5	04	13.3	400	5800	1600	23200	75	2.953	0.281	0.189	001C-04	N
TFN002KN05	5/16"	8	05	14.8	400	5800	1400	20300	85	3.346	0.327	0.220	001C-05	N
TFN002KN06	3/8"	9.5	06	17.1	400	5800	1320	19140	90	3.543	0.418	0.281	001C-06	N
TFN002KN08	1/2"	12.7	08	20.4	400	5800	1100	15950	130	5.118	0.525	0.353	001C-08	N
TFB002KN04	1/4"	6.5	04	13.3	400	5800	1600	23200	75	2.953	0.281	0.189	001C-04	B
TFB002KN05	5/16"	8	05	14.8	400	5800	1400	20300	85	3.346	0.327	0.220	001C-05	B
TFB002KN06	3/8"	9.5	06	17.1	400	5800	1320	19140	90	3.543	0.418	0.281	001C-06	B
TFB002KN08	1/2"	12.7	08	20.4	400	5800	1100	15950	130	5.118	0.525	0.353	001C-08	B

Marking: Available only embossed