

PPC Complete Systems for analogue Hydraulic Testers PPC-04-plus / PPC-PAD-light

B



Complete System PPC-04-plus-SET (PPC-04-plus)



Complete System PPC-PAD-light-SET (PPC-PAD-light)

Product Description

The PPC complete systems are assembled in different versions according to customer requirements. All complete systems are supplied in a handy case with customised foam inserts and offer space for the components listed below:

Components

Standard Options for Complete Systems PPC-04-plus

- 1x Case-PPC-04-plus/PAD-light
- 1x Hydraulic Tester PPC-04-plus
- 1x Power supply incl. country-specific adaptor Power-Supply-PPC-PAD-light-MULTI
- Up to 3 Pressure Sensor-PPC-04/12-P with installed adaptors for STAUFF Test 20 (M16 x 2)
- 1x Temperature Sensor-PPC-04/12-T-M02 with installed SGV-16S-G-W3 (optional)
- Up to 2 connection cables (3 m / 9.84 ft)
- 3x Adaptors SAD for the STAUFF Test 15/12/10 series
- 1x USB cable 1m (USB A to Micro-USB)
- 1x Quick guide with link to: PC software and instructions

Standard Options for Complete Systems PPC-PAD-light

- 1x Case-PPC-04-plus/PAD-light
- 1x Hydraulic Tester PPC-PAD-light
- 1x Power supply incl. country-specific adaptor Power-Supply-PPC-PAD-light-MULTI
- Up to 3 Pressure Sensors with installed adaptors STAUFF Test 20 (M16 x 2)
- 1x Temperature Sensor-PPC-04/12-T-M02 with installed SGV-16S-G-W3 (optional)
- Up to 4 connection cables (3 m / 9.84 ft)
- 3x Adaptors SAD for the STAUFF Test 15/12/10 series
- 2x USB cable 1m (USB A to C and USB C to C)
- 1x Quick guide with link to: PC software and instructions

Order Codes

PPC	-	PAD-light-SET	-	T	-	015 / 150 / 600	-	CAL
①		②		③		④		⑤
① Series and Type		② Version		③ Temperature Sensor		④ Pressure Range and Pressure Sensor		⑤ Pressure Range and Pressure Sensor
Hydraulic Tester		PPC-04-plus		without Temperature Sensor T and SGV		1. Pressure Sensor		2. Pressure Sensor
		PPC-PAD-light		with Temperature Sensor T and SGV				3. Pressure Sensor
				(none)				see table
				T				see table
		04-plus-SET						see table
		PAD-light-SET						see table
								without calibration certificate (none)
								with calibration certificate (factory calibration) CAL

Pressure Range and Pressure Sensor

Pressure Range	Pressure Sensor		
000	When ordering a complete system with one or two pressure sensors, specify „000“ for the pressure range of the 2. and / or 3. pressure sensors.		
015	Pressure Range 1. Pressure Sensor	Pressure Range 2. Pressure Sensor	Pressure Range 3. Pressure Sensor
060			
150			
400			
600			
601			
z.B.	015 (15 bar)	060 (60 bar)	000 (0 bar)
Please keep in mind that two pressure sensors with identical measuring ranges are necessary for differential pressure measurements.			

Alternative

If you need more space in the case for your components, STAUFF offers the **Case-PPC-PAD-plus** as an alternative. This can hold several measuring devices at the same time and offers a variety of storage options (at least 9 pressure sensors and 2 flow turbines and much more). The case is only available individually. The contents must be ordered separately.

