


Relief, A to T



TECHNICAL DATA

Body Type	Sandwich
Interface	ISO 07
Body Features	A to T with gage port
Stack Height	1.97 in.
Seal Plate Included (see notes)	Yes
Open Cavities	1
Cavity	T-3A
Port Size	1/4" NPTF
Model Weight	3.03 lb.

CONFIGURATION

/M Modifier 6061-T651 Aluminum, Metric,
Buna-N

- NOTES**
- Stack height value in technical data table includes seal retainer plate.
 - Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

Modifiers	Ports
CKA, /10, /11, /15, /16, /V	Gage Port (Plugged): 1/4" NPTF;
CKA/1A, /1B, /1F, /1G, /M, /Z	Gage Port (Plugged): 1/4" BSPP;

INCLUDED COMPONENTS

Part	Description	Quantity
330-018-002	Plug	1
500-001-111	O-Ring	2
500-001-118	O-Ring	4
700-006	Seal Plate	1
811-001-006	Pin	2
A330-006-010	SAE Plug	1

CONFIGURATION OPTIONS

Model Code Example: CKAArray

MODIFIER (M)

/M	6061-T651 Aluminum, Metric, Buna-N
	6061-T651 Aluminum, Buna-N
/10	6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
/11	6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
/15	6061-T651 Aluminum, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II
/16	6061-T651 Aluminum, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
/1A	6061-T651 Aluminum, Metric, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
/1B	6061-T651 Aluminum, Metric, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
/1F	6061-T651 Aluminum, Metric, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II
/1G	6061-T651 Aluminum, Metric, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
/V	6061-T651 Aluminum, Viton
/Z	6061-T651 Aluminum, Metric, Viton
/S	65-45-12 Ductile Iron, Buna-N, Dewatering Oil
/S3	65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer
/S4	65-45-12 Ductile Iron, Buna-N, Chem. Black
/S5	65-45-12 Ductile Iron, Buna-N, Electroless Nickel
/T	65-45-12 Ductile Iron, Metric, Buna-N, Dewatering Oil
/T3	65-45-12 Ductile Iron, Metric, Buna-N, Trivalent Clear Zinc with Top Sealer
/T4	65-45-12 Ductile Iron, Metric, Buna-N, Chem. Black
/T5	65-45-12 Ductile Iron, Metric, Buna-N, Electroless Nickel
/W	65-45-12 Ductile Iron, Metric, Viton, Dewatering Oil
/W3	65-45-12 Ductile Iron, Metric, Viton, Trivalent Clear Zinc with Top Sealer
/W4	65-45-12 Ductile Iron, Metric, Viton, Chem. Black
/W5	65-45-12 Ductile Iron, Metric, Viton, Electroless Nickel
/Y	65-45-12 Ductile Iron, Viton, Dewatering Oil
/Y3	65-45-12 Ductile Iron, Viton, Trivalent Clear Zinc with Top Sealer
/Y4	65-45-12 Ductile Iron, Viton, Chem. Black
/Y5	65-45-12 Ductile Iron, Viton, Electroless Nickel