



This clamp is manufactured in AISI 430 with an additional matt-black surface treatment which increases its corrosion resistance.

Thanks to the surface treatment, this clamp can be mounted discreetly in any application, making it a favourite in automotive or motorcycle applications.

The geometry, band, stamping, housing and screw are identical to other ASFA clamps, meaning that the performance is not altered in any way.

DIN 3017. The Black ASFA SW3 hose clip complies fully with the DIN 3017 norm, and also with the directive EU 20027957EC.

MATERIAL: Stainless steel band and housing W3 AISI 430 X6Cr17 (DIN 1.4016)
Stainless steel W4 AISI 304 Cu screw

FINISH: Delta Seal Black
CORROSION RESISTANCE: 250 hours Salt Spray (ASTM B-117)

Part Number	Ø Application mm	A +0.3-0.2	L +1-0.5	S ±0.1	H Max.	B Max.	Maximum values		Box Quantity	Outer Box Quantity
							Pressure (Bar)	Par (Nm)		
73016206	16-27	12	29,6	0,8	11	16,7	45,0	4,5	50	400
73016214	20-32	12	29,6	0,8	11	16,7	45,0	5,5	50	400
73016222	25-40	12	29,6	0,8	11	16,7	40,0	5,5	50	400
73016230	30-45	12	29,6	0,8	11	16,7	35,0	5,5	50	400
73016249	32-50	12	29,6	0,8	11	16,7	35,0	6,0	50	200
73016257	40-60	12	29,6	0,8	11	16,7	30,0	6,0	50	400
73016265	50-70	12	29,6	0,8	11	16,7	25,0	7,0	50	400
73016273	60-80	12	29,6	0,8	11	16,7	20,0	7,0	50	50
73016281	70-90	12	29,6	0,8	11	16,7	17,0	7,0	50	50
73016290	80-100	12	29,6	0,8	11	16,7	14,0	7,0	25	200
73016302	90-110	12	29,6	0,8	11	16,7	12,0	7,0	25	200
73016310	100-120	12	29,6	0,8	11	16,7	10,0	7,0	25	200
73016329	110-130	12	29,6	0,8	11	16,7	8,0	7,0	25	25
73016337	120-140	12	29,6	0,8	11	16,7	7,0	7,0	25	25
73016345	130-150	12	31,6	0,8	11	16,7	6,0	7,0	25	25
73016353	140-160	12	31,6	0,8	11	16,7	6,0	7,0	25	25
73016361	150-170	12	31,6	0,8	11	16,7	6,0	7,0	25	25
73016379	160-180	12	31,6	0,8	11	16,7	3,0	7,0	10	10
73016387	170-190	12	31,6	0,8	11	16,7	3,0	7,0	10	10
73016396	180-200	12	31,6	0,8	11	16,7	2,0	7,0	10	10