

Vaterteil Typ F nach MIL A-A-59326A mit BSPT Außengewinde

Male adapter type F - MIL A-A-59326A with male BSPT thread

Adaptateur type F fileté mâle BSPT - MIL A-A-59326A

Camlock tipo F: acople macho - rosca macho BSP

Męczyzna Typ F - MIL A-A-59326A - Wtyk z gwintem zewnętrznym BSPT

Camlock tipo F: versione maschio filettato maschio BSPT



Part-No.	Material	WP	Dimension	Thread	Price
F075x050PP	Polypropylene	8,5 bar	DN20	1/2"	
F075PP	Polypropylene	8,5 bar	DN20	3/4"	
F100PP	Polypropylene	8,5 bar	DN25	1"	
F125PP	Polypropylene	6,5 bar	DN32	1 1/4"	
F150x125PP	Polypropylene	6,5 bar	DN40	1 1/4"	
F150PP	Polypropylene	6,5 bar	DN40	1 1/2"	
F200PP	Polypropylene	6,5 bar	DN50	2"	
F300PP	Polypropylene	5 bar	DN80	3"	
F400PP	Polypropylene	5 bar	DN100	4"	

Vaterteil Typ F nach MIL A-A-59326A mit BSPT Außengewinde (90° Bogen)

Male adapter type F - MIL A-A-59326A with male BSPT thread (90° Elbow)

Adaptateur type F fileté mâle BSPT - MIL A-A-59326A (90° Coude)

Camlock tipo F: acople macho - rosca macho BSPT (90° Codo)

Męczyzna Typ F - MIL A-A-59326A - Wtyk z gwintem zewnętrznym BSPT (90° Łolanoz)

Camlock tipo F: versione maschio filettato maschio BSPT (90° Curva)



Part-No.	Material	WP	Dimension	Shank	Price
F200PP-90	Polypropylene	6,5 bar	DN50	51mm	

