


Filclair AL coloured



Flexible and polyvalent reinforced pvc hose with food grade quality. Suitable for a large number of media: industrial gasses or liquids, and food stuffs. Filclair can be used in vacuum up to Ø25mm.

Temperature: -15°C to +60°C

- **Tube:** colored pvc with food grade quality
- **Reinforcement:** high tensile textile thread
- **Cover:** colored pvc with food grade quality, standard transparent blue and red, other on demand

Certificat: IANESCO RE 11/10484 dated 10/08/2011

Attention:

- transport of food products following simulations A, B and C of the certificate, with the exception of alcoholic solutions > 20°
- not suitable for hydrocarbons and derivatives

ATTENTION: forbidden for the use with fatty food stuffs (vegetal oils, milk, ...)

Applications

supply of compressed air for machinery
industrial gases and liquids
light chemical products

Assembly

all types of industrial couplings
assembly with hose-clamps

Ref red	Ref blue	Diameter (mm)	Bending radius (mm)	Weight (g/m)	Working Pressure (bar)	Burst Pressure (bar)	Coil length (m)
FCRT0612	FCBT0612	6 x 12	55	110	15	50	50
FCRT0814	FCBT0814	8 x 14	60	130	15	50	50
FCRT0915	FCBT0915	9 x 15	65	141	15	50	50
FCRT1016	FCBT1016	10 x 16	75	155	15	50	50
FCRT1219	FCBT1219	12 x 19	80	216	15	50	50
FCRT1320	FCBT1320	13 x 20	90	225	15	50	50
FCRT1523	FCBT1523	15 x 23	100	308	15	50	50
FCRT1624	FCBT1624	16 x 24	110	319	15	50	50
FCRT1927	FCBT1927	19 x 27	125	363	15	50	50



FCRT2028	FCBT2028	20 x 28	130	372	15	50	50
		25 x 34	150	524	15	50	50
FCRT2534*	FCBT2534*						
FCRT2536	FCBT2536	25 x 36	160	622	15	50	50
FCRT3040	FCBT3040	30 x 40	180	670	12	50	50

Product ID: 12072

Source URL: <https://www.alfaflex.com/en/products/10000/12000/filclair-al-gekleurd-0>