



Equal Tee
Type FI-T ▪ Series LL / L / S



D

Ordering Codes

***FI-T*-10*L*-W3*-MS**

- * Equal Tee **FI-T**
- * Outside Tube Diameter D1 (in mm) **-10**
- * Series **LL**
 - Extra-Light Series
 - Light Series **L**
 - Heavy Series **S**
- * Material Code Steel, zinc/nickel-plated **-W3**
- Please contact STAUFF for alternative materials and surface finishings.
- * Assembling / Kitting **—**
 - Fitting body only
 - Fitting body supplied with cutting rings and union nuts **-MS**
 - Fitting body supplied with soft-sealing cutting rings and union nuts **-MSV**

Series	Tube OD mm D1	PN bar	Dimensions						Weight kg ca. per 100	Ordering Codes ³
			mm D2	L	L1 ¹	L2	S1	S2		
LL	4	100	3	15	42	11	9	10	1,00	FI-T-04LL-W3
	6	100	4,5	15	42	9,5	9	12	1,23	FI-T-06LL-W3
	8	100	6	17	46	11,5	12	14	1,91	FI-T-08LL-W3
	10	100	8	21,5	54	16	14	17	3,42	FI-T-10LL-W3
L	12	100	10	21,5	59	15	14	19	3,80	FI-T-12LL-W3
	6	500	4	19	54	12	12	14	2,66	FI-T-06L-W3
	8	500	6	21	58	14	12	17	3,17	FI-T-08L-W3
	10	500	8	22	60	15	14	19	4,06	FI-T-10L-W3
	12	400	10	24	64	17	17	22	5,52	FI-T-12L-W3
	15	400	12	28	72	21	19	27	9,98	FI-T-15L-W3
	18	400	15	31	80	23,5	24	32	14,83	FI-T-18L-W3
	22	250	19	35	88	27,5	27	36	18,81	FI-T-22L-W3
	28	250	24	38	94	30,5	36	41	30,44	FI-T-28L-W3
	35	250	30	45	112	34,5	41	50	49,27	FI-T-35L-W3
	42	250	36	51	126	40	50	60	72,20	FI-T-42L-W3
	S	6	800	4	23	62	16	12	17	4,60
8		800	5	24	64	17	14	19	6,21	FI-T-08S-W3
10		800	7	25	68	17,5	17	22	7,92	FI-T-10S-W3
12		630	8	29	76	21,5	17	24	10,88	FI-T-12S-W3
14		630	10	30	80	22	19	27	12,97	FI-T-14S-W3
16		630	12	33	86	24,5	24	30	10,97	FI-T-16S-W3
20		420	16	37	96	26,5	27	36	25,58	FI-T-20S-W3
25		420	20	42	108	30	36	46	44,75	FI-T-25S-W3
30		420	25	49	124	35,5	41	50	68,20	FI-T-30S-W3
38		420	32	57	144	41	50	60	108,00	FI-T-38S-W3

Connecting Parts

- Cutting Ring
Type **FI-DS** Page 28
- Soft-Sealing Cutting Ring
Type **FI-WDDS** Page 29
- Support Sleeve
Type **FI-VH** Page 31
- STAUFF Form EVO Sealing Ring
Type **FI-FD** Page 32
- Union Nut
Type **FI-M** Page 33
- 37° Flared Tube Fitting Set
Type **FI-AB** Page 37

¹ Approximate dimension in assembled condition.

² Weight excluding cutting rings and union nuts.

³ Standard scope of delivery: Fitting body only.