



TECHNICAL DATA

Maximum Coil Temperature at 68°F (20°C) Ambient	218°F (105°C)
Arc Suppression (TVS)	Included
Power Consumption (cold) - at rated voltage	22 watts
Maximum Ambient Temperature	122 °F
Voltage/Frequency	28 VDC
Operating Voltage Range	+/- 10% nominal
Duty Cycle Rating	100 %
Connector	Deutsch DT04-2P
Connector Environment Rating	IP69K
Solenoid Tube Diameter	.75 in.
Coil Nut Torque	4.5 lbf in.
Model Weight	0.53 lb.

PROPORTIONAL PERFORMANCE DATA

Maximum Current	510 mA
-----------------	--------

USED WITH

DMDA DMDAS DNCA DNDA DNDAS DNDC DNDY DNDYS FMDA 991723001

991723002

TECHNICAL FEATURES

- Coil windings utilize Class N, (392° F [200 °C] rated) magnet wire.
- A TVS surge suppression diode is built into DC coils. Nominal breakdown voltage: 68V. Model code 1.5 KE68CA Steady state power dissipation @ 75°C is 6.5 W and peak pulse dissipation is 1500 W for 1 ms, nonrepetitive.
- Power cable with mating connector is required and is not included with product.
- The Deutsch DT04-2P connector satisfies the requirements of thermal shock tests. In this test, the coil is energized to achieve its stabilized temperature and then immediately immersed into ice cold water. This process is repeated 5 times, after which, the insulation resistance of the coils should not fall below 10 megohms.
- The coil is magnetically symmetrical and can be mounted in either direction on the solenoid tube without affecting performance.
- IP rating is dependent on the coil connector and the mating connector used.
- RoHS compliant. Restricted materials less than 0.1% total by weight.
- The external steel shell is plated with clear zinc trivalent.