

Hypress 2TE

APPLICATIONS :



TFE02TEI



APPLICABLE SPECIFICATIONS

EN 854 2TE

Braided hose textile.

Inner tube: Oil resistant synthetic rubber.

Reinforcement: 1 textile braid.

Coverage: Synthetic rubber resistant to oils, fuels and atmospheric conditions.

Recommended fluids: Mineral and biological oils, glycol-water based, water, lubricants.

working temperature: from -40 to +100° C petroleum based fluids, from -40 to +70° C for water based fluids, from 0 to +70°C water.

Product number	ID		Dimension	OD	Max WP		Min BP		Min BR		Weight (approx)		Ferrule
	in	mm	dash size		bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFE02TEI03	3/16"	4.8	03	11.8	80	1160	320	4640	35	1.378	0.118	0.079	0003-03
TFE02TEI04	1/4"	6.4	04	13.4	75	1088	300	4350	40	1.575	0.140	0.094	0007-04
TFE02TEI05	5/16"	8	05	14.9	68	986	272	3944	50	1.969	0.154	0.103	0007-05
TFE02TEI06	3/8"	9.5	06	16.5	63	914	252	3654	60	2.362	0.179	0.120	0007-06
TFE02TEI08	1/2"	12.7	08	19.7	58	841	232	3364	70	2.756	0.226	0.152	0007-08
TFE02TEI10	5/8"	16	10	23.9	50	725	200	2900	90	3.543	0.312	0.210	0007-10
TFE02TEI12	3/4"	19	12	27	45	653	180	2610	110	4.331	0.342	0.230	0007-12
TFE02TEI16	1 "	25.4	16	34.4	40	580	160	2320	150	5.906	0.483	0.325	0007-16

Marking: White ink branded (customization not possible)