


Soft-Sealing Cutting Ring Type FI-WDDS • Series L / S



B

Series	Tube OD (mm/in)	PN (bar/PSI)	Dimensions (mm/in)	Weight (kg/lbs) ca. per 100	Ordering Codes
	D1		L1		Soft-Sealing Cutting Ring
L	6	500	8,8	0,19	FI-WDDS-06L/S-V-W3
	.24	7250	.35	.42	
	8	500	8,8	0,24	FI-WDDS-08L/S-V-W3
	.31	7250	.35	.53	
	10	500	9,8	0,35	FI-WDDS-10L/S-V-W3
	.39	7250	.39	.77	
	12	400	9,8	0,41	FI-WDDS-12L/S-V-W3
	.47	5800	.39	.90	
	15	400	10,2	0,66	FI-WDDS-15L-V-W3
	.59	5800	.40	1.44	
	18	400	10,2	0,82	FI-WDDS-18L-V-W3
	.71	5800	.40	1.79	
	22	250	11,5	1,06	FI-WDDS-22L-V-W3
	.87	3625	.45	2.34	
	28	250	11,5	1,28	FI-WDDS-28L-V-W3
	1.10	3625	.45	2.82	
	35	250	13,5	2,36	FI-WDDS-35L-V-W3
	1.38	3625	.53	5.18	
	42	250	13,5	2,75	FI-WDDS-42L-V-W3
	1.65	3625	.53	6.05	
S	6	800	8,8	0,19	FI-WDDS-06L/S-V-W3
	.24	11600	.35	.42	
	8	800	8,8	0,24	FI-WDDS-08L/S-V-W3
	.31	11600	.35	.53	
	10	800	9,8	0,35	FI-WDDS-10L/S-V-W3
	.39	11600	.39	.77	
	12	630	9,8	0,41	FI-WDDS-12L/S-V-W3
	.47	9135	.39	.90	
	14	630	10,2	0,73	FI-WDDS-14S-V-W3
	.55	9135	.40	1.61	
	16	630	10,3	0,83	FI-WDDS-16S-V-W3
	.63	9135	.41	1.82	
	20	420	12,5	1,28	FI-WDDS-20S-V-W3
	.79	6091	.49	2.81	
	25	420	12,5	1,58	FI-WDDS-25S-V-W3
	.98	6091	.49	3.48	
	30	420	13,5	2,41	FI-WDDS-30S-V-W3
	1.18	6091	.53	5.31	
	38	420	13,5	3,00	FI-WDDS-38S-V-W3
	1.50	6091	.53	6.60	

Ordering Codes

***FI-WDDS*-15*L*-V*-W3**

* Soft-Sealing Cutting Ring	FI-WDDS
* Outside Tube Diameter D1 (in mm)	-15
* Series	Light Series L Heavy Series S
* Seal Material	FKM (Viton®) -V
* Material Code	Steel, zinc/nickel-plated -W3

Please contact STAUFF for alternative materials and surface finishings.

Standard seal material is FKM (Viton®).

