



## JS1-H JOYSTICK

[83053707](#) 

Model code: JS1H-XY-CPH-S-C34-TPP2-L-V1A-NNN-B1A-B1A-R1A-NNN-NNN-NNN-NNN-NNN-NNN-R1A-BRGN-NN

[Where to buy](#) 

## Product specifications

Characteristic	Value	Description
B: Operational axis	XY	XY: Bi-direct.: X and Y axis
C: Shaft pos. sensing output	CPH	CPH: CAN Open w. hall
D: Centering spring	S	S: Standard spring
E: CAN	C34	C34: Node ID 34, 250Kbs
F1: Mounting	T	T: Top mounting/NBR BOOT
F2: Handle	PP2	PP2: IP66 version of PR2
G: Left- or right hand	L	L: Left hand grip
H1: Defining of front plate	V1A	V1A: Roller hall, 5mm
H2: Defining of front plate	NNN	NNN: No function
H3: Defining of front plate	B1A	B1A: Black K12
H4: Defining of front plate	B1A	B1A: Black K12
H5: Defining of front plate	R1A	R1A: Red K12
H6: Defining of front/back	NNN	NNN: No function
H7: Defining of back side	NNN	NNN: No function
H8: Defining of back side	NNN	NNN: No function
H9: Def. of grip front side	NNN	NNN: No function
H10: Def. of grip front side	NNN	NNN: No function
H11: Def. of grip front side	NNN	NNN: No function
H12: Def. of grip side	R1A	R1A: Red K12
J1: Grip color	B	B: Black grip & front
J2: Ring	R	R: Red colour band



Characteristic	Value	Description
J3: Connector	G	G: Cable for CAN P/H (1 plug)
J4: Kit and ext. Cable	N	N: No ext. Cable or ring
K: Software or settings	NN	NN: No software and settings

## General specifications

Characteristic	Value
Proposition 65	Cancer and Reproductive Harm

**For the most current information and other product assets, please use this link to visit the product page on Danfoss PowerSource [🔗](#)**