



Mutterteil Typ B - MIL A-A-59326A mit BSPT Außengewinde mit NBR Dichtung

Female coupler type B - MIL A-A-59326A with male BSPT thread - NBR gasket

Coupleur type B fileté mâle BSPT - MIL A-A-59326A - Joint NBR

Camlock tipo B: acople hembra - rosca macho BSPT - Junta NBR

Kobieta Typ B - MIL A-A-59326A - Gniazdo z gwintem zewnętrznym BSPT - NBR Uszczelka

Camlock tipo B: versione femmina filettata maschio - Guarnizione NBR

Part-No.	Material	WP	Dimension	Thread	Price
B050SS2	SS316/CF8M	10 bar	DN15	1/2"	
B075SS	SS316/CF8M	10 bar	DN20	3/4"	
B100SS	SS316/CF8M	10 bar	DN25	1"	
B125SS	SS316/CF8M	10 bar	DN32	1 1/4"	
B150SS	SS316/CF8M	10 bar	DN40	1 1/2"	
B200SS	SS316/CF8M	10 bar	DN50	2"	
B250SS	SS316/CF8M	10 bar	DN65	2 1/2"	
B300SS	SS316/CF8M	10 bar	DN80	3"	
B400SS	SS316/CF8M	7 bar	DN100	4"	
B500SS	SS316/CF8M	5 bar	DN125	5"	
B600SS	SS316/CF8M	5 bar	DN150	6"	



Mutterteil Typ B - MIL A-A-59326A mit BSPT Außengewinde Sicherheitsverschluss System Self-Lock - NBR Dichtung

Female coupler type B - MIL A-A-59326A with male BSPT thread - System Self-Lock - NBR gasket

Coupleur type B fileté mâle BSPT - MIL A-A-59326A - Système Self-Lock - Joint NBR

Camlock tipo B - Security: acople hembra - rosca macho BSPT - Anillas de seguridad - Junta NBR

Kobieta Typ B - MIL A-A-59326A - Gniazdo z gwintem zewnętrznym BSPT - Samozamykacz systemowy - NBR Uszczelka

Camlock tipo B - Security: versione femmina filettata maschio - Anello di sicurezza autobloccante - Guarnizione NBR

Part-No.	Material	WP	Dimension	Thread	Price
B200SS-SLL	SS316/CF8M	10 bar	DN50	2"	
B300SS-SLL	SS316/CF8M	10 bar	DN80	3"	
B400SS-SLL	SS316/CF8M	7 bar	DN100	4"	

