



PUR Hose Kits – with Series 300

ARO 210 Standard, 5.5mm

- Series 300 couplings and nipples
- Flexible PUR hose with long service life
- Pre-assembled and ready to use

CEJN Hose Kits come pre-assembled and ready for immediate use. They consist of an extremely flexible, straight braided or spiral polyurethane (PUR) hose combined with Series 300 Standard or eSafe couplings and nipples with reusable Stream-Line connections.

PUR Hose Kits are also available with Series 310, 320 and 410 Standard or Vented Safety couplings and nipples.



Flow capacity is measured at 100 PSI (6.9 bar) inlet pressure, and pressure drop at 6 PSI (0.4 bar).

		Service length	Part No.	ID x OD	Max working pressure
SERIES 300	Spiral	6.6 °F (2.0 m)	19 958 9977	(5x8 mm)	145 PSI (10 bar)
		13.1 °F (4.0 m)	19 958 9948	(6.5x10 mm)	145 PSI (10 bar)
		19.7 °F (6.0 m)	19 958 9952	(6.5x10 mm)	145 PSI (10 bar)
	Straight Braided	32.8 °F (10.0 m)	19 958 9802	(8x12 mm)	232 PSI (16 bar)
		49.2 °F (15.0 m)	19 958 9842	(8x12 mm)	232 PSI (16 bar)
SERIES 300, ESAFE	Spiral	6.6 °F (2.0 m)	19 958 9739	(6.5x10 mm)	145 PSI (10 bar)
			19 958 9330	(8x12 mm)	145 PSI (10 bar)
		13.1 °F (4.0 m)	19 958 9740	(6.5x10 mm)	145 PSI (10 bar)
			19 958 9712	(8x12 mm)	145 PSI (10 bar)
			19 958 9345	(11x16 mm)	145 PSI (10 bar)
	Straight Braided	19.7 °F (6.0 m)	19 958 9741	(6.5x10 mm)	145 PSI (10 bar)
			19 958 9713	(8x12 mm)	145 PSI (10 bar)
		26.2 °F (8.0 m)	19 958 9742	(6.5x10 mm)	145 PSI (10 bar)
			19 958 9714	(8x12 mm)	145 PSI (10 bar)
			19 958 9782	(11 x 16 mm)	145 PSI (10 bar)
			19 958 9704	(8x12 mm)	232 PSI (16 bar)
	49.2 °F (15.0 m)	19 958 9705	(8x12 mm)	232 PSI (16 bar)	
	32.8 °F (10.0 m)	19 958 9335	(9.5x13.5 mm)	145 PSI (10 bar)	
	49.2 °F (15.0 m)	19 958 9336	(9.5x13.5 mm)	145 PSI (10 bar)	



CEJN Safety

CEJN reserves the right to make changes without further notification. Thread connections are listed according to ISO Standards. Other connections and sealing material on request. Check with an authorized CEJN distributor for availability and prices. Some part numbers may be subject to minimum order quantities. Please visit our website, www.cejn.com, for general maintenance tips.

AIR FLOW

- HOSE 5X8 MM
- HOSE 6.5X10 MM
- HOSE 8X12 MM
- HOSE 9.5X13.5 MM
- HOSE 11X16 MM

