


PIPE SCREW JOINTS A MALE STUD COUPLINGS

THE WORLD OF TUBE FITTINGS

AP MALE STUD COUPLINGS BSP TAPER

BSP taper.



description	pipe OD	PN series	S	S ₁	L ₁	l ₁	i	G	kg % pc
DS-AP 6-L/R 1/8"	6	L 315 (1260)	12	14	30.0	15.0	8	R 1/8" K	2.2
DS-AP 8-L/R 1/4"	8	L 315 (1260)	17	17	35.0	20.0	12	R 1/4" K	3.8
DS-AP 10-L/R 1/4"	10	L 315 (1260)	17	19	37.0	22.0	12	R 1/4" K	4.3
DS-AP 12-L/R 3/8"	12	L 315 (1260)	19	22	37.0	22.0	12	R 3/8" K	6.0
DS-AP 15-L/R 1/2"	15	L 315 (1260)	24	27	40.0	25.0	14	R 1/2" K	10.3
DS-AP 18-L/R 1/2"	18	L 315 (1260)	27	32	42.0	25.5	14	R 1/2" K	12.7
DS-AP 22-L/R 3/4"	22	L 160 (640)	32	36	46.0	29.5	16	R 3/4" K	18.5
DS-AP 28-L/R 1"	28	L 161 (640)	41	41	51.5	34.5	18	R 1" K	25.8
DS-AP 35-L/R 1 1/4"	35	L 162 (640)	50	50	56.0	34.5	20	R 1 1/4" K	41.5
DS-AP 42-L/R 1 1/2"	42	L 163 (640)	55	60	61.0	38.0	22	R 1 1/2" K	56.7

L₁ = approximate length with nut tightened

Please see "Engineering and technical data - Selecting the correct tube fitting" for more information on pressure.