

Description

Item No.

DRILL-PUMP

universal pump for electric drills, stainless steel shaft, housing cover in brass, pump housing and vanes of glass reinforced plastic. Suitable for diesel, light fuel oil, water, anti-freeze, neutral emulsions. Please check for compatibility with other fluids.

max. drive speed: up to 2.500 l/min., max.output 20 l/min.,
suction height: up to 1.5 m, hose connection 1", axle \varnothing 8 mm

DRILL-PUMP

34 305 80



EP 12 / EP 24

self priming electric vane pump, thread 3/4" (female), IP 54, 1.5 bar, with clips for battery terminals, suitable for diesel and light heating oil

EP 12: 12 V DC, 0.12 kW, 16 A, approx. 36 l/min. (at free delivery)
EP 24: 24 V DC, 0.12 kW, 8 A, approx. 40 l/min. (at free delivery)

EP 12

34 304 05

EP 24

34 304 29



EP 55

self priming vane pump with integral by-pass pressure regulator, anti syphon valve, mains cable, nozzle holster, 2" BSP bung adaptor

output: approx. 55 l/min. (at free delivery)
max. pressure: approx. 2 bar
electric data: 230 V, 50 Hz, IP55, 0.46 kW
suction height: 2.5 m

EP 55

34 315 01

without accessories (threads 1" female)

EP 55

34 315 18

with bung adaptor and nozzle holster



EP 60

self priming vane pump with integral bypass pressure regulator, 2 m mains cable, designed for vegetable oil and products up to 500 cSt.

output: approx. 60 l/min. (at free delivery)
max. pressure: approx. 6 bar (87 psi)
electric data: 230 V, 50 Hz, IP55, 1.6 kW
threads: R1" male
suction height: up to 2.5 m

EP 60

34 310 20



Description

Item No.

EP 140

self priming electric vane pump with integral by-pass pressure regulator, 3 m mains cable, on/off switch

output:	approx. 80 l/min. (at free delivery)
max. pressure:	approx. 2.5 bar (36 psi)
electric data:	230 V, 50 Hz, IP55, 0.5 kW
threads:	inlet and outlet 1" BSP (male)
suction height:	up to 2.5 m



EP 140

34 382 10

EP 12 PLUS

self priming electric vane pump with integral by-pass pressure regulator, 3 m mains cable and clips for battery terminals

output:	approx. 80 l/min. (at free delivery)
max. pressure:	approx. 1.6 bar (23 psi)
electric data:	12 V DC, IP55, 0.37 kW
threads:	inlet and outlet 1" BSP (male)
suction height:	up to 2.5 m



EP 12 PLUS

34 380 12

EP 24 PLUS

self priming electric vane pump with integral by-pass pressure regulator, 3 m mains cable and clips for battery terminals

output:	approx. 80 l/min. (at free delivery)
max. pressure:	approx. 1.6 bar (23 psi)
electric data:	24 V DC, IP55, 0.37 kW
threads:	inlet and outlet 1" BSP (male)
suction height:	up to 2.5 m



EP 24 PLUS

34 381 28

Description

Item No.

AP 40L, not self priming

universal electric drum pump, ready to use transfer pump kit with priming lever, 2" BSP and M64 x 4 bung adaptor, suitable for water, Anti-Freeze, diesel and light hydraulic oils

with 1.8 m connection cable

Kit also includes:

- 3-part telescopic suction tube (480 - 1100 mm)
- 2.5 m reinforced delivery hose
- filler nozzle and hose clips

AP 40L/230:	230 V AC/50 Hz	0.20 kW / 0.9 A, approx. 30 l/min
AP 40L/12:	12 V DC	0.11 kW / 9.2 A, approx. 25 l/min
AP 40L/24:	24 V DC	0.125 kW / 5.2 A, approx. 25 l/min

AP 40L/230	34 303 44
------------	-----------

AP 40L/12	34 303 06
-----------	-----------

AP 40L/24	34 303 20
-----------	-----------



EP 12 / EP 24 - Electric Pump Kit

self priming electric vane pump for connection to a battery, for storage tanks on construction sites and in agriculture, suitable for use with diesel and light heating oil (contact us for compatibility w. other fluids)

delivery pressure 1.5 bar, delivery hose 3.5 m DN 20 3/4", plastic suction hose 1.5 m 3/4" x 19, trigger nozzle S deluxe

EP 12:	12 V DC, 120 W, 16 A, approx. 36 l/min (at free delivery)
EP 24:	24 V DC, 120 W, 8 A, approx. 40 l/min (at free delivery)

EP 12 Electric pump kit	34 304 12
-------------------------	-----------

EP 24 Electric pump kit	34 304 36
-------------------------	-----------



EP 55-S - Tank Kit

Tank kit includes:

- pump EP 55 (technical details see page 120),
- 1.5 m reinforced suction hose DN 20 (3/4") with suction filter and foot valve
- 4 m or 8 m delivery hose DN 20 (3/4")
- suction and delivery hose with swivel nuts for easy and safe fitting
- nozzle with swivel

EP 55-S-4	34 319 45
-----------	-----------

EP 55-S-8	34 319 83
-----------	-----------



EP 55-S - Tank Kit with Meter

Tank kit includes:

- pump EP 55 (technical details see p. 120),
- 1.5 m reinforced suction hose DN 20 (3/4") with suction filter and foot valve
- 4 m or 8 m delivery hose DN 20 (3/4")
- suction and delivery hose with swivel nuts for easy and safe fitting
- flow meter DIGIMET M80 mechanical counter
- resettable dispense volume 0-999 litre, 6 digit totaliser

EP55-S-4 with meter	34 319 52
---------------------	-----------

EP55-S-8 with meter	34 319 90
---------------------	-----------



Description

Item No.

EP 55-AZS Tank Kit

tank kit includes:

- pump EP 55 (technical details see p. 120), output 55 l/min (free flow)
- 1.5 m reinforced suction hose DN 20 (3/4") with suction filter and backlash valve
- 4 m or 8 m delivery hose DN 20 (3/4")
- suction and delivery hose with swivel nuts for easy and safe fitting
- automatic shut-off nozzle AZS/80 l with swivel

tank not included

(please check according to local regulations)

versions also available on request with automatic nozzle with type approval according to DIN EN 13012 (see page 126)

EP55-AZS-4

34 320 41

EP55-AZS-8

34 320 89



EP 55-AZS Tank Kit with Meter

tank kit as described above, but with:

- flow meter DIGIMET M80 mechanical counter, resettable dispense volume 0-999 litre, 6 digit totaliser

tank not included

(please check according to local regulations)

versions also available on request with automatic nozzle with type approval according to DIN EN 13012 (see page 126)

EP55-AZS-4 with meter

34 320 58

EP55-AZS-8 with meter

34 320 96



Description

Item No.

EP 55-AZS-T - Tank Kit

tank kit includes:

- pump EP 55 (technical details see p. 120), output 55 l/min (free flow)
- double-wall safety-tank with transportation approval 1.000 l
- 1.5 m reinforced suction hose DN 20 (3/4") with suction filter and backlash valve
- 4 m or 8 m delivery hose DN 20 (3/4")
- suction and delivery hose with swivel nuts for easy and safe fitting
- automatic shut-off nozzle AZS/80 l with swivel

supplied with tank, pump-kit pre-installed

(please check according to local regulations)

versions also available on request with automatic nozzle with type approval according to DIN EN 13012 (see page 126)

EP 55-AZS-T-4

34 322 01

EP 55-AZS-T-8

34 322 25



EP 55-AZS-T - Tank Kit with Meter

tank kit as described above, but with:

- flow meter DIGIMET M80 mechanical counter, resettable dispense volume 0-999 litre, 6 digit totaliser

supplied with tank, pump-kit pre-installed

(please check according to local regulations)

versions also available on request with automatic nozzle with type approval according to DIN EN 13012 (see page 126)

EP 55-AZS-T-4 with meter

34 323 00

EP 55-AZS-T-8 with meter

34 323 24



Description

Item No.

EP 140-AZS - Tank Kit

tank kit includes:

- pump EP 140 (technical details see p. 121), output 80 l/min (free flow)
- 1.5 m reinforced suction hose DN 25 (1") with suction filter and backlash valve
- 4 m or 8 m delivery hose DN 25 (3/4")
- **suction and delivery hose with swivel nuts for easy and safe fitting**
- **automatic shut-off nozzle AZS/120 l with swivel**

(Please check according to local regulations. Versions also available on request with automatic nozzle with type approval according to DIN EN 13012, see page 126)

tank, pump bracket and drip tray not included

EP 140-AZS-4

34 324 09

EP 140-AZS-8

34 324 16

EP 140-AZS - Tank Kit with Meter

tank kit as described above, but with **flow meter DIGIMET M80 mechanical counter**, resettable dispense volume 0-999 litre, 6 digit totaliser

(Please check according to local regulations. Versions also available on request with automatic nozzle with type approval according to DIN EN 13012, see page 126)

tank, pump bracket and drip tray not included

EP 140-AZS-4 with meter

34 324 61

EP 140-AZS-8 with meter

34 324 78

EP 140-AZS-T - Tank Kit

tank kit as described above, but with **double-wall safety-tank with transportation approval 1.000 l**, drip tray with retainer, pump-kit bracket

(Please check according to local regulations. Versions also available on request with automatic nozzle with type approval according to DIN EN 13012, see page 126)

supplied with tank, pump-kit pre-installed

EP 140-AZS-T-4

34 325 15

EP 140-AZS-T-8

34 325 22

EP 140-AZS-T - Tank Kit with Meter

tank kit as described above, but with **flow meter DIGIMET M80 mechanical counter**, resettable dispense volume 0-999 litre, 6 digit totaliser

(Please check according to local regulations. Versions also available on request with automatic nozzle with type approval according to DIN EN 13012, see page 126)

supplied with tank, pump-kit pre-installed

EP 140-AZS-T-4 with meter

34 325 53

EP 140-AZS-T-8 with meter

34 325 60

