

Swivels - Series 9000 and 9100



©HydraSpecma · HSCO_Swivels-9000-9100-EN · 10.2021

Swivels are mainly used when hoses need to be turned under pressure. By using swivels, twisting of the hoses can be avoided. Keep in mind that 7° rotation of a hose can shorten the life span of the product by 90%.

These swivels can be used for slow rotation or oscillating movement. To avoid unnecessary wear of the swivels, radial loads must be avoided. The 9000/9100 series is a cost-effective choice when you want to avoid downtime and reliability is paramount.


Series 9000, Swivel Straight, Female/Male-BSPP

Item no.	Thread Female/Male (T)	Max pressure (bar)	Length mm (L)	Hex (E)	Hex (E1)
9000-04	G 1/4"	400	61	30	19
9000-06	G 3/8"	400	66	34	24
9000-08	G 1/2"	300	71	36	27
9000-12	G 3/4"	300	80	45	34
9000-16	G 1"	300	90	50	41
9000-20	G 1 1/4"	300	101	55	50
9000-24	G 1 1/2"	300	110	65	55
9000-32	G 2"	250	118	75	65


Series 9100, Swivel 90°, Female/Male-BSPP

Item no.	Thread Female/Male (T)	Max pressure (bar)	Length mm (L)	Hex (E)
9100-04	G 1/4"	400	69	19
9100-06	G 3/8"	400	76	24
9100-08	G 1/2"	300	87	27
9100-12	G 3/4"	300	100	34
9100-16	G 1"	300	113	41
9100-20	G 1 1/4"	300	121	50
9100-24	G 1 1/2"	300	143	55
9100-32	G 2"	250	151	65


1/4" - 1/2"



3/4" - 2"



1/4" - 1"



1 1/4" - 2"

