

INTERPUMP MARATHON 2SC

THEOM2K



APPLICATIONS :



APPLICABLE SPECS. :

IMM - EXCEED EN 857 2SC - ISO 11237 2SC

NO-SKIVE hose. Exceed EN specification. Impulse tested up to 1.000.000 cycles.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glycol-water based, water, lubricants.

Operating temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70°C for water based fluids, from 0 to +70°C water.

													
Part number	ID		Size	OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm		mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE0M2K-04	1/4"	6.4	4	13.3	450	6525	1800	26100	50	1.969	0.285	0.192	001C-04
THE0M2K-05	5/16"	8.0	5	14.8	420	6090	1680	24360	60	2.362	0.33	0.222	001C-05
THE0M2K-06	3/8"	9.5	6	17.1	385	5583	1540	22330	70	2.756	0.422	0.284	001C-06
THE0M2K-08	1/2"	12.7	8	20.4	350	5075	1500	21750	80	3.150	0.566	0.349	001C-08
THE0M2K-10	5/8"	16.0	10	23.5	350	5075	1400	20300	90	3.543	0.665	0.447	001C-10
THE0M2K-12	3/4"	19.0	12	27.6	280	4060	1120	16240	120	4.725	0.865	0.531	001C-12
THE0M2K-16	1"	25.4	16	36.0	250	3625	1000	14500	140	5.512	1.39	0.934	0022-16

Lengths exc

Available on request:

with MSHA cover, in case of order use our part no. THEMM2K

with MSHA and smooth cover, in case of order use our part no. THESM2K

with antiabrasion cover, in case of order use our part no. THEPM2KI

MARKING: Available "embossed" Code THEOM2KN.