



Mutterteil Typ D - MIL A-A-59326A mit BSPP Innengewinde

Sicherheitsverschluss System Self-Lock mit NBR Dichtung

Female coupler type D - MIL A-A-59326A with female BSPP thread - System Self-Lock - NBR gasket

Coupleur type D taraudé femelle BSPP - MIL A-A-59326A - Système Self-Lock - Joint NBR

Camlock tipo D - Security: acople hembra - rosca hembra BSPP - Anillas de seguridad - Junta NBR

Kobieta Typ D - MIL A-A-59326A - Gniazdo z gwintem wewnętrznym BSPP - System samoblokujący - NBR Uszczelka

Camlock tipo D - MIL A-A-59326 A con filettatura femmina BSPP - Anelli di sicurezza autobloccante - Guarnizione NBR

Part-No.	Material	WP	Dimension	Thread	Price
D200AL-SL	Aluminum	10 bar	DN50	2"	
D300AL-SL	Aluminum	10 bar	DN80	3"	
D400AL-SL	Aluminum	7 bar	DN100	4"	

Vaterteil Typ E - MIL A-A-59326A mit Stutzen für Schelleneinband

Male adapter type E - MIL A-A-59326A with grooved hose-shank

Adaptateur type E douille annelée sans collerette - MIL A-A-59326A

Camlock tipo E: acople macho - espiga para manguera

Męczyzna Typ E - MIL A-A-59326A - Wtyk z karbowaną końcówką do węża do mocowania opaskami

Camlock tipo E: versione maschio portagomma



Part-No.	Material	WP	Dimension	Shank	Price
E050AL	Aluminum	10 bar	DN15	13mm	
E075AL	Aluminum	10 bar	DN20	21mm	
E100AL	Aluminum	10 bar	DN25	27mm	
E125AL	Aluminum	10 bar	DN32	34mm	
E150AL	Aluminum	10 bar	DN40	40mm	
E200AL	Aluminum	10 bar	DN50	51mm	
E250AL	Aluminum	10 bar	DN65	64mm	
E300AL	Aluminum	10 bar	DN80	76mm	
E400AL	Aluminum	7 bar	DN100	103mm	
E500AL	Aluminum	5 bar	DN125	128mm	
E600AL	Aluminum	5 bar	DN150	152mm	
E800AL	Aluminum	4 bar	DN200	200mm	

