

Medium Pressure

EHA505

Medium Duty Air



Application

- Medium duty air service
- Pneumatic tools

Markets

- Construction
- Mining
- Rental industry
- Oil and gas exploration
- In-plant air service

Construction

Tube Oil-mist resistant SBR rubber

Reinforcement

High-tensile synthetic textile

Cover Abrasion, ozone, and weather resistant SBR rubber blend

Colors Black (BK), Yellow (YW)

Operating temperature

-25°C to +70°C
(-13°F to +158°F)

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHA505-04BK	6.0	0.25	13	0.51	20.0	290	64.0	928	0.16	0.11	100	330
EHA505-05BK	8.0	0.31	15	0.59	20.0	290	64.0	928	0.20	0.13	100	330
EHA505-06BK	10.0	0.39	18	0.71	20.0	290	64.0	928	0.27	0.18	100	330
EHA505-08BK	13.0	0.50	22	0.87	20.0	290	64.0	928	0.40	0.27	100	330
EHA505-10BK	16.0	0.63	25	0.98	20.0	290	64.0	928	0.45	0.30	100	330
EHA505-12BK	19.0	0.75	29	1.14	20.0	290	64.0	928	0.59	0.40	100	330
EHA505-16BK	25.0	1.00	37	1.46	20.0	290	64.0	928	1.89	1.27	100	330