

For the SWIVELLING version add the suffix "/SO" at the P/N.  
For example:  
440/10/SO

### FIXED PAINTED STEEL



### Supplied with:

- hose in black synthetic rubber with galvanized steel coupling
- swivel joint in brass or galvanized steel
- Viton® or Polyurethane seals
- central shaft in galvanized steel
- inlet hose from 0,6 m to 1 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	Hose supplied	Connection		
			Inlet	Outlet	
S. 440	Air-Water 20 bar	440/10	without hose	F 1/2"G	F 1/2"G
		440/11	15m 1/2" (962/15)	F 1/2"G	M 1/2"G
		440/12	12m 3/8" (952/13)	F 1/2"G	M 3/8"G
		440/13	18m 3/8" (952/19)	F 1/2"G	M 3/8"G
		440/14	10m 1/2" (962/10)	F 1/2"G	M 1/2"G
S. 4440 ABS	Air-Water 20 bar	4440/10	without hose	F 1/2"G	F 1/2"G
		4440/11	15m 1/2" (962/15)	F 1/2"G	M 1/2"G
		4440/12	12m 3/8" (952/13)	F 1/2"G	M 3/8"G
		4440/13	18m 3/8" (952/19)	F 1/2"G	M 3/8"G
		4440/14	10m 1/2" (962/10)	F 1/2"G	M 1/2"G
S. 440	Oil 150 bar	440/40	without hose	F 1/2"G	F 1/2"G
		440/41	10m 1/2" (963/11)	F 1/2"G	M 1/2"G
		440/42	15m 1/2" (963/15)	F 1/2"G	M 1/2"G
S. 4440 ABS	Oil 150 bar	4440/40	without hose	F 1/2"G	F 1/2"G
		4440/41	10m 1/2" (963/11)	F 1/2"G	M 1/2"G
		4440/42	15m 1/2" (963/15)	F 1/2"G	M 1/2"G
S. 440	Grease 400 bar	440/50	without hose	F 3/8"G	F 1/2"G
		440/51	12m 1/4" (935/13)	F 3/8"G	M 1/4"G
		440/52	18m 1/4" (935/18)	F 3/8"G	M 1/4"G
		440/55	10m 3/8" (957/10)	F 3/8"G	M 1/4"G
		440/56	15m 3/8" (957/15)	F 3/8"G	M 1/4"G
S. 4440 ABS	Grease 400 bar	4440/50	without hose	F 3/8"G	F 1/2"G
		4440/51	12m 1/4" (935/13)	F 3/8"G	M 1/4"G
		4440/52	18m 1/4" (935/18)	F 3/8"G	M 1/4"G
		4440/55	10m 3/8" (957/10)	F 3/8"G	M 1/4"G
		4440/56	15m 3/8" (957/15)	F 3/8"G	M 1/4"G



Atex 94/9

- ▶ II 3GD c X (only for S. 4440 ABS and S. 440 Air-Water 20 bar)
- ▶ IIB 2GD c T4 T135°C X

## USES

