


AUßENGEWINDE - SCHLAUCHNIPPEL

Type 8054

BSP, 60° Innen-Konus, passend für Schlauchnippel nach DIN 3863, Type 8010 und 8014

NIPPLE WITH OUTSIDE THREAD

BSP, 60° inner cone fits for hose nipples according to DIN 3863, type 8010 and type 8014



DN (NW)	für Schlauch- Innen-Ø for hose inside Ø mm	SW mm	Gewinde thread	L 1 mm	L 2 mm	Bestell-Nr. part-no
3/4	5 - 6	13	G 1/8"	17	11	8054.0304
6	7 - 8	17	G 1/4"	17	11	8054.0600
8	9 - 10	19	G 3/8"	19	12	8054.0800
13	14 - 15	24	G 1/2"	21	14	8054.1300
16	17 - 18	27	G 5/8"	22	14	8054.1600
20	21 - 22	30	G 3/4"	24	16	8054.2000
20/16	17 - 18	30	G 3/4"	24	16	8054.2016
25/20	21 - 22	36	G 1"	32	20	8054.2520

AUßENGEWINDE - SCHLAUCHNIPPEL

Type 8057

Einschraubzapfen nach DIN 3852, mit Dichtkante

Type 8058

NIPPLE WITH OUTSIDE THREAD

with screw in pivot according to DIN 3852, with sealing surface



DN (NW)	für Schlauch-Innen-Ø for hose inside Ø mm	SW mm	Gewinde thread	L 1 mm	L 2 mm	Bestell-Nr. part-no
8/10	11 - 12	22	M 16 x 1,5	21,0	12	8057.0810
10	11 - 12	24	M 18 X 1,5	21,5	12	8057.1000
4	5 - 6	14	G 1/8"	14,5	8	8058.0304
6	7 - 8	19	G 1/4"	20,0	12	8058.0600
6/4	5 - 6	19	G 1/4"	20,0	12	8058.0604
8	9 - 10	22	G 3/8"	19,0	12	8058.0800
8/6	7 - 8	22	G 3/8"	20,0	12	8058.0806
13	14 - 15	27	G 1/2"	23,5	14	8058.1300
13/10	11 - 12	27	G 1/2"	23,5	14	8058.1310
20	21 - 22	32	G 3/4"	27,0	16	8058.2000
20/13	14 - 15	32	G 3/4"	27,0	16	8058.2013
20/16	17 - 18	32	G 3/4"	27,0	16	8058.2016